

36

Unit Information

| | Weatherproof/Food-Safe Remote Heads | | | |
|---------------------------------|-------------------------------------|------------|---------------------------------|---------------------------------|
| | Lamp Volts | Lamp Watts | Single Head with Mounting Plate | Double Head with Mounting Plate |
| Incandescent PAR-36 Sealed Beam | 6 | 8 | 36WP6-8 | 36WPDH6-8 |
| | 6 | 18 | 36WP6-18 | 36WPDH6-18 |
| | 6 | 25 | 36WP6-25 | 36WPDH6-25 |
| | 12 | 18 | 36WP12-18 | 36WPDH12-18 |
| | 12 | 25 | 36WP12-25 | 36WPDH12-25 |
| | 12 | 30* | 36WP12-30 | 36WPDH12-30 |
| Halogen PAR-36 Sealed Beam | 6 | 6 | H36WP6-6 | H36WPDH6-6 |
| | 6 | 8 | H36WP6-8 | H36WPDH6-8 |
| | 6 | 12 | H36WP6-12 | H36WPDH6-12 |
| | 6 | 20 | H36WP6-20 | H36WPDH6-20 |
| | 12 | 8 | H36WP12-8 | H36WPDH12-8 |
| | 12 | 12 | H36WP12-12 | H36WPDH12-12 |

*Spot Pattern

36WP & H36WP SERIES WEATHERPROOF/FOOD-SAFE

Single 5" PAR-36 Weatherproof Neoprene lamp housing with clear Lexan Lens Guard. Ideal for food-safe areas. Gasketed, die cast mounting plate mounts to 4" round box. Fully assembled with swivel and lead wires.



36WPDH & H36WPDH SERIES WEATHERPROOF/FOOD-SAFE

Double 5" PAR-36 Weatherproof Neoprene lamp housings with clear Lexan Lens Guards. Ideal for food-safe areas. Gasketed, die cast mounting plate mounts to single gang box. Fully assembled with swivel and lead wires.



Unit Information

| | Recessed Remote Gimbal Fixture | | |
|----------------------------|--------------------------------|------------|--------------------------|
| | Lamp Volts | Lamp Watts | Single Head with Housing |
| Halogen PAR-36 Sealed Beam | 6 | 8 | H36GF6-8 |

36GF SERIES

Remote recessed gimbal fixture with single PAR-36 sealed beam lamp. Gimbal ring adjusts to 30° in four directions. Matte white trim ring. 5.75" Diameter Finished Opening. 8.31" Diameter Trim Size. 5.75" x 4.75" D Housing Dimension.



Option

Add Suffix to Catalog Number

-EM Emergency Mode

SPECIAL LAMP WATTAGES

All Emergency Lights are furnished with standard lamps of the wattage shown on the individual catalog pages. If a special lamp wattage is required, refer to the lamp selection charts below, and add the wattage suffix number to the product model number.

NOTE: Not all lamps are interchangeable. Check voltage, capacity, and head housing type before making selection. All PAR-36 lamps are sealed beams and must be supplied in a round head housing.

Example: Model No. 2CL6S16: Standard with (2) rectangular heads with 6V HIT lamps.

Required: (2) Halogen 20-watt lamps. Change Model No. to: H2CL6S16-20.

| HIT Lamp Wattages | | | | |
|-------------------|--------------------------------|----|-----|-----|
| System Voltage | Suffix Number for Lamp Wattage | | | |
| 6V | -6 | -7 | -9 | |
| 12V | -7 | -9 | -12 | -18 |

| Tungsten Sealed Beam PAR-36 Lamp Wattages | | | | |
|---|--------------------------------|------|------|--|
| System Voltage | Suffix Number for Lamp Wattage | | | |
| 6V | -S8 | -S18 | -S25 | |
| 12V | -S18 | -S25 | -S35 | |

| Halogen Sealed Beam PAR-36 Lamp Wattages | | | | |
|--|--------------------------------|-----|-----|-----|
| System Voltage | Suffix Number for Lamp Wattage | | | |
| 6V | -6 | -8 | -12 | -20 |
| 12V | -8 | -12 | | |