

## 36

### Unit Information

	Weatherproof/Food-Safe Remote Heads			
	Lamp Volts	Lamp Watts	Single Head with Mounting Plate	Double Head with Mounting Plate
Incandescent PAR-36 Sealed Beam	6	8	36VP6-8	36VPDH6-8
	6	18	36VP6-18	36VPDH6-18
	6	25	36VP6-25	36VPDH6-25
	12	18	36VP12-18	36VPDH12-18
	12	25	36VP12-25	36VPDH12-25
	12	30*	36VP12-30	36VPDH12-30
Halogen PAR-36 Sealed Beam	6	6	H36VP6-6	H36VPDH6-6
	6	8	H36VP6-8	H36VPDH6-8
	6	12	H36VP6-12	H36VPDH6-12
	6	20	H36VP6-20	H36VPDH6-20
	12	8	H36VP12-8	H36VPDH12-8
	12	12	H36VP12-12	H36VPDH12-12

\*Spot Pattern

### 36WP & H36WP SERIES WEATHERPROOF/FOOD-SAFE

Single 5" PAR-36 Weatherproof Neoprene lamp housing with clear Lexan Lens Guard. Ideal for food-safe areas. Gasketed, die cast mounting plate mounts to 4" round box. Fully assembled with swivel and lead wires.



### 36WPDH & H36WPDH SERIES WEATHERPROOF/FOOD-SAFE

Double 5" PAR-36 Weatherproof Neoprene lamp housings with clear Lexan Lens Guards. Ideal for food-safe areas. Gasketed, die cast mounting plate mounts to single gang box. Fully assembled with swivel and lead wires.



### Unit Information

	Recessed Remote Gimbal Fixture		
	Lamp Volts	Lamp Watts	Single Head with Housing
Halogen PAR-36 Sealed Beam	6	8	H36GF6-8

### 36GF SERIES

Remote recessed gimbal fixture with single PAR-36 sealed beam lamp. Gimbal ring adjusts to 30° in four directions. Matte white trim ring. 5.75" Diameter Finished Opening. 8.31" Diameter Trim Size. 5.75" x 4.75" D Housing Dimension.



### Option

Add Suffix to Catalog Number  
**-EM** Emergency Mode

### SPECIAL LAMP WATTAGES

All Emergency Lights are furnished with standard lamps of the wattage shown on the individual catalog pages. If a special lamp wattage is required, refer to the lamp selection charts below, and add the wattage suffix number to the product model number.

**NOTE:** Not all lamps are interchangeable. Check voltage, capacity, and head housing type before making selection. All PAR-36 lamps are sealed beams and must be supplied in a round head housing.

**Example:** Model No. 2CL6S16: Standard with (2) rectangular heads with 6V HIT lamps.

**Required:** (2) Halogen 20-watt lamps. Change Model No. to: H2CL6S16-20.

HIT Lamp Wattages		
System Voltage	Suffix Number for Lamp Wattage	
6V	-6	-7 -9
12V	-7	-9 -12 -18

Tungsten Sealed Beam PAR-36 Lamp Wattages		
System Voltage	Suffix Number for Lamp Wattage	
6V	-S8	-S18 -S25
12V	-S18	-S25 -S35

Halogen Sealed Beam PAR-36 Lamp Wattages		
System Voltage	Suffix Number for Lamp Wattage	
6V	-6	-8 -12 -20
12V	-8	-12