

## 4X



E4XLD1RW



H2E4XLD1RW

### Dimensions

#### WITHOUT HEADS

Height: 9.5"  
Width: 11.5"  
Depth: 5.5"

#### WITH HEADS

Height: 9.5"  
Width: 21.6"  
Depth: 5.5"

### Options

Add Suffix to Catalog Number

- 277** 277VAC Input
- HTR** Heater
- MK** Mounting Kit for End or Ceiling Mount
- QC** Quik-Chek™ Remote Test & Time Delay (For Emergency Signs Only)



Made in USA



### Series Features



#### NEMA APPLICATIONS

- All Units Satisfy the Requirements of NEMA 1, 2, 3, 3R, 4 & 4X Enclosures



#### Choice of Light Source

Incandescent	2,000 Hours
Fluorescent	10,000 Hours
LED (Indirect View)	25+ Years
LED (Direct View)	25+ Years



- Designed for Use in Corrosive, Dirty or Damp Environments

- Back Mount Standard

- Universal Stencil Face

- Directional Chevron Snapouts

- Lite Grey Fiberglass Housing

- Meets or Exceeds UL 924

### Additional Emergency Unit Features

- Integrated Solid State System

- Constant Current, Automatic Charger



- Low-Voltage Battery Cutoff

- Brownout Sensitivity

- AC Lockout (Line Latching)



- Mounted Lighting Heads Available:

Choice of 8-Watt Incandescent or Halogen Sealed Beam Lamps

- (2) 6-Volt, 6-Watt HIT Lamps (E4X, E4XP or E4XL)



- Sealed Battery

- 6-Volt Operation

- Maintenance-Free



- Test Switch

- Red (Power On & Charge) Indicator

### Unit Information

Series	Light Source	Standard Voltage	Max. Input Watts (120VAC)		Max. Input Watts (277VAC)		Illumination Time (Hrs.)		Replacement Battery	
			Less Heads	With Heads	Less Heads	With Heads	Less Heads	With Heads	Less Heads	With Heads
<b>AC Only</b>										
4X	Incandescent		120V*	24W	N/A	30W	N/A	N/A	N/A	N/A
N/A										
4XP	Fluorescent	120V*	20W	N/A	30W	N/A	N/A	N/A	N/A	N/A
4XL	LED (Indirect)		120/277V		1.7W	N/A	1.7W	N/A	N/A	N/A
N/A	N/A									
4XLD	LED (Direct)		120/277V		3.6W	N/A	3.6W	N/A	N/A	N/A
N/A	N/A									
<b>Emergency</b>										
E4X	Incandescent		120V*	26W	30W	26W	30W	1.5	1.5	S65

\*For 277VAC – See Options

### Ordering Information

H	2	E4XLD	1	R	W	-QC
Halogen Lamp Prefix	Lamp Heads on Unit Blank – None	Series 4X-AC/INC. 4XP-AC/FL 4XL-AC/LED 4XLD-AC/LED E4X-EM/INC. E4XP-EM/FL E4XL-EM/LED E4XLD-EM/LED	# Faces 1	Letter Color R – Red G – Green	Panel Color W – White B – Black	Options Factory Options