



Die Cast Diffused LED Exits

DCL

Series Features

	<ul style="list-style-type: none"> 120/277 VAC Operation
	<ul style="list-style-type: none"> Maximum Input Rating 120 VAC 60 Hz .028 Amps 277 VAC 60 Hz .01 Amps
	<ul style="list-style-type: none"> Light-Emitting Diodes – 25+ Year Life Illuminates with Uniform Color and Brightness Indirect Placement for Diffused Legend Output
	<ul style="list-style-type: none"> Contemporary Styling Canopy Standard
	<ul style="list-style-type: none"> Die Cast Aluminum Construction Thin-Edge Black Housing Brushed Aluminum Stencil Face Directional Chevron Snapouts Suitable For Damp Location UL Listed



DCL/EDCL

Accessories

Order Separately

- 63** Wire Guard (for Single-Face Back Mount Only)
- VDS** Vandal-Deterrent Shield (for Single-Face Back Mount Only)

Dimensions

DCL/EDCL
 Height: 8.50"
 Width: 12.81"
 Depth: 1.875"

CANOPY ONLY
 Height: 4.38"
 Width: 5.50"
 Depth: 0.625"

Additional Emergency Unit Features

	<ul style="list-style-type: none"> Integrated Solid State System Constant Current, Controlled Automatic Charger Circuit Low-Voltage Battery Cutoff Brownout Sensitivity
	<ul style="list-style-type: none"> Increased LED Brightness Level in Emergency Mode
	<ul style="list-style-type: none"> Sealed Nickel Cadmium Battery 10-Year Battery Warranty Maintenance-Free
	<ul style="list-style-type: none"> Test Switch Red (Power On) Indicator

Ordering Information

DCL	2	R	A	B	U
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
DCL – AC EDCL – Emer.	2	Red	Aluminum	Black	Universal

