



## Lead Calcium Battery Information

- Completely Sealed
- Maintenance-Free
- Absorbent Separator used to Immobilize Electrolyte (Non-Gel)
- Lead Calcium Grid Provides Longer Life and Greater Reliability
- Quick Disconnect Terminal Size Prevents Improper Connection
- Dual Inner Seal and Outer Cover Provides Maximum Leakage Protection
- High-Impact Synthetic Resin (ABS)
- 6-Month Shelf Life
- 5–7 Years Expected Life in 60°–80°F Operating Range (16°–27°C)

## Unit Information

Model Number	DC Volts	Amp* Hour	Watts per Hour						Dimensions (In.)			
			1.5	2	3	4	6	8	L	W	H	Term.
S65	6	4.6	12	9	6	–	–	–	2.8	1.9	4.0	0.2
S68	6	7.0	18	14	9	7	–	–	6.0	1.4	3.7	0.3
S610SL	6	10.0	32	24	16	12	8	6	6.0	2.0	3.7	0.3
S636	6	33.0	100	75	50	38	25	18	7.2	3.0	6.6	–
S650	6	50.0	120	90	60	45	30	22	7.4	4.5	8.1	–
S1215	12	17.0	100	75	50	36	25	18	7.2	3.0	6.6	–
S1220	12	22.0	130	100	65	50	32	25	6.9	6.6	5.0	–

Discharge to 87.5% Nominal System Voltage at 68°F Ambient Temperature

\*20 Hour Rate

Battery Data May Change Without Notice



## Refillable Lead Acid Battery Information

- Provides Greatest Capacity per Dollar
- Dry Charged for Extended Shelf Life
- No Capacity Loss in Storage
- Refillable for Extended Operating Life
- Low Antimony, Extra Thick Positive Plates
- Flame-Arrestor Vent Caps
- Optional Hydrocaps Minimize Water Losses & Extend Service Intervals
- Specific Gravity Indicator(s) Provide Charge Status
- Cast Lead Terminals with Hardware
- 5-Year Shelf Life
- 8–12 Years Expected Life in 32°–105°F Operating Range (0°–41°C)

## Unit Information

Model Number	DC Volts	Amp* Hour	Watts per Hour						Dimensions (In.)			
			1.5	2	3	4	6	8	L	W	H	Term.
L640	6	40	120	90	60	45	30	28	10.3	10.3	5.30	7.40
L6100	6	100	360	240	180	120	90	60	0	0	6.70	8.00
L6100S	6	100	360	240	180	120	90	60	9.00		6.70	8.00
L1260	12	64	240	180	120	90	60	45	9.00		6.90	8.10

Discharge to 87.5% Nominal System Voltage at 68°F Ambient Temperature

\*20 Hour Rate

Battery Data May Change Without Notice

## Sealed Nickel Cadmium Battery Information

- Completely Sealed
- Maintenance-Free
- Active Plate Materials: Nickel Oxide and Metallic Cadmium
- Cylindrical Shape in Fence Construction
- Positive and Negative Lead Wires with Plug-In Connectors
- 5-Year Shelf Life
- 8–10 Years Expected Life in -4°–158°F  
Operating Range (-20°–70°C)



## Unit Information

Model Number	DC Volts	Amp Hr.	Watts Per Hour						Dimensions		
			1.5	2	3	4	6	8	L	W	H
N51F	4.8	1.3	4.8	3.8	2.4	—	—	—	3.8	0.9	1.8
N67F	6	7	18	14	9	7	—	—	6.3	1.3	3.6
N71F	7.2	0.6	4	3	2	—	—	—	4	0.7	1.7
N127	12	7	36	28	18	14	9	7	6.3	2.6	3.6

Battery Data May Change Without Notice

## Refillable Nickel Cadmium Battery Information

- Battery Filled with Potassium Hydroxide, an Alkaline Solution
- Specific Gravity Does Not Reflect Charged Battery Condition
- 1.180 Nominal Specific Gravity when Filled to Top Level Line
- Immune to Accidental Overcharge
- No Corrosive Fumes
- Refillable for Extended Operating Life
- Nickel Plated, Steel Positive Plates for Low Self-Discharge Rate
- Flame Arrestor Vent Caps
- Nickel-Plated Steel Terminal Post & Hardware
- 20–25 Years Expected Life in -22°–140°F  
Operating Range (-30°–60°C)



## Unit Information

Model Number	DC Volts	Amp* Hour	Watts per Hour						Dimensions (In.)			
			1.5	2	3	4	6	8	L	W	H	Term.
N640	6	40	100	75	50	32	24	20	9.5	4.8	10.8	
N650	6	50	120	85	55	40	28	20	9.5	4.8	10.8	

Discharge to 87.5% Nominal System Voltage at 68°F Ambient Temperature

\*20 Hour Rate

Battery Data May Change Without Notice