

## Series Features




- Integrated Solid State System
- Internal Battery Charger
- 12 Hour Recharge Time
- Maximum Input Rating  
120 VAC 60 Hz 0.35 Amps



- PAR-36 Halogen Sealed Beam Lamps



- Sealed Lead Calcium Battery
- 6 Volt Operation
- Maintenance-Free



- Rugged 20-Gauge Steel Housing
- Safety Yellow Powder Coat Finish
- Fully Secured Battery
- Full-Length Piano Hinge
- Ammeter
- External On/Off Switch, One For Each Lamp
- Top Mounted Carrying Handle
- Detachable 6ft 120V Cord

## Unit Information

Model Number	Std. Lamp Watt	Run Time	Weight	Replacement Battery
HBL6S5	6	1.5 hr s	10	( 1 ) S65
HBL6S8	6	2.5 hr s	11	( 1 ) S68
HBL6S10	6	4 hr s	14	( 1 ) S610SL
HBL6S20	6	8 hr s	20	( 2 ) S610SL
HBL6S36	6	12 hr s	22	( 1 ) S636
HBL6S20- 20	20	2 hr s	17	( 2 ) S610SL
HBL6S36- 20	20	3.75 hr s	22	( 1 ) S636
BL12S15- 100	100	.75 hr s	22	( 1 ) S1215

## HBL



Portable Industrial Work Light comes in handy in situations where a back-up generator fails to start. Can be positioned anywhere in a facility that requires lighting during an outage – especially in critical areas.

### Dimensions

**HBL**  
 Height: 13.5"  
 Width: 13.5"  
 Depth: 4.75"



Made in USA