

# Commercial Emergency Lights

## BRITELITE



### Dimensions

#### BRITELITE

Height: 11.25"  
Width: 8.5"  
Depth: 3.75"

The Britelite is great for use in Offices, Hotels, Apartments, Condo Buildings, and any Commercial space where attractiveness and reliability are prime concerns.



### Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 0.20 Amps  
277VAC 60 Hz 0.20 Amps



- High-Intensity Tungsten Lamps, 6-watt



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free



- Innovative Architectural Design
- Injection Molded Polycarbonate Housing
- High Impact, White Finish
- Red (Power On) LED Indicator Light
- Test Switch
- Damp Location
- UL 924 Listed

### Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
BRITELITE	6	12	-	-	-	-	-	-	-	(1) S65

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.