

Series Features



- 120/277 VAC Operation
- 1.5 Hours of Emergency Illumination
- Integrated Solid State System
- Constant Current, Controlled, Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity



- Maximum Input Rating (120 or 277VAC)
Standard 2.5 Watts

EMERGENCY LIGHT

- (2) 6VDC, 4-Watt HIT Lamps (PH)
(Total 8 Watts)
- (2) 6VDC, 4-Watt PAR-36 HIT Lamps
(Total 8 Watts)
- LED (Indirect)
 - (1) Strip, 120/277 VAC, 2.5-Watt
 - (2) Strips, (-DS), 120/277 VAC, 3.5-Watt
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Increased LED Brightness Level in Emergency Mode



- Sealed Lead Calcium Battery
- 6-Volt Operation (S65)
- Maintenance-Free



- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- 20-Gauge Steel Housing
- Polycarbonate Lamp Enclosures (-PH)
- White Powder-Coat Finish
- Easy Installation
- Amber (Power On) Indicator
- Test Switch
- UL Listed

COM



COM-PH

Rectangular Heads



COM

Round Heads

Options

Add Suffix to Catalog Number

- DS Double LED Strip
- HI High-Intensity LEDs
- U Universal Face
(Additional Backplate – Double-Face Signs Only)

Dimensions

HOUSING

Height: 13.3"
Width: 12.3"
Depth: 2.3"

(Add 12.5" to the Overall Width Dimension for Round-Head Models)



Made in USA

Ordering Information

2	COM	1	R	W	W	-PH	U
Emergency Light	Series	# Faces	Letter Color	Stencil Color	Housing Color	Head Type	Options
2	COM	1 2	R ed G reen	W hite	W hite	Blank – Rnd. PH – Plastic Head	Factory Options