

Series Features



- 120VAC Operation Standard
- Maximum Input Rating
120VAC 24 Watts
277VAC 30 Watts



- Long-Life Incandescent
- (2) 140VAC, 15-Watt Lamps



- Ceiling, End or Back Mount
- Canopy Standard on Double-Face Sign
- Universal Stencil
- Directional Chevron Snapouts
- Prismatic Downlight Lens
- Die Cast Aluminum Housing
- Matte Black Frame
- Brushed Aluminum Stencil Face
- UL Listed

Additional Emergency Unit Features



- Integrated Solid State System
- Constant Current Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Maximum Input Rating
120VAC 26 Watts
277VAC 30 Watts



- Long-Life Incandescent
- (2) 6 VDC, 3-Watt Lamps



- Sealed Nickel Cadmium Battery
- 6-Volt Operation
- Maintenance-Free



- Canopy (with Electronics & Battery)
- Test Switch
- Red (Power On) Indicator

Ordering Information

EDX	2	R	A**	B	-OF
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
DX – AC EDX – Emer.	1 2	R ed G reen W hite	W hite B lack A luminum	W hite B lack	Factory Options

*Standard

**Background Panel Color on Open-Face Signs

DX



DX



EDX

Options

Add Suffix to Catalog Number

- 6 (2) 6VDC Lamps for AC/6VDC Remote Operation
- 12 (2) 12VDC Lamps for AC/12VDC Remote Operation
- 277 277VAC Input
- 2CKT (2) Independent AC Circuits
- CPY Canopy (Single-Face DX)
- OF Open-Face Panel (Fiber Std.)
- RMB Recessed Mount Black (DX Only)
- RMW Recessed Mount White (DX Only)
- TP Tamper-Proof Screws

Dimensions

DX/EDX

Height: 8.3"
Width: 13.3"
Depth: 2.4"

DX CANOPY

Length: 4.7"
Width: 4.7"
Depth: 0.8"

EDX CANOPY

Length: 9.0"
Width: 4.7"
Depth: 2.3"

Accessories

Order Separately

- 63 Wire Guard (for Single-Face, Back Mount DX Only)
- VDS Vandal-Deterrent Shield (for Single-Face, Back Mount DX Only)



UL 924 LISTED



Made in USA