



Options

Add Suffix to Catalog Number

- 6** (2) 6VDC Lamps for AC/6VDC Remote Operation
- 12** (2) 12VDC Lamps for AC/12VDC Remote Operation
- CPY** Canopy (For Single-Face Signs)
- DMP** Damp Location Listing (Damp Label)
- DS** Double LED Strips for Increased Illumination or 2 Independent AC Circuit Operation
- HI** High-Intensity LEDs
- NY** New York City Approved with 8" Letters
- RMB** Recessed Mount Trim Kit, Black
- RMW** Recessed Mount Trim Kit, White
- TP** Tamper-Proof Faceplate

Master/Slave Options:

- SL** Slave (Requires Single-Face EDXLS as Power Source)
- REC/S** Recessed Mounting for Slave Only
- REC/M** Recessed Mounting for Master Only
- REC/MS** Recessed Mounting for Master and Slave

Accessories

Order Separately

- 63** Wire Guard (for Single-Face Back Mount Only)
- VDS** Vandal-Deterrent Shield (for Single-Face Back Mount Only)

DXLS/EDXLS

Dimensions

DXLS/EDXLS

Height: 8.3"
Width: 12.0"
Depth: 2.3"

CANOPY ONLY




Height: 4.7"
Width: 4.7"
Depth: 0.8"

NEW YORK CITY





Height: 11.0"
Width: 14.5"
Depth: 2.3"



Series Features

- 
 - 120/277 VAC Operation
 - Maximum Input Rating (120 or 277VAC)
Standard 1.7 Watts
DS Option 3.5 Watts
- 
 - Light-Emitting Diodes – 25+ Year Life
 - Illuminates with Uniform Color and Brightness
 - Indirect Placement for Diffused Legend Output
- 
 - Contemporary Styling
 - Canopy Standard on Double-Face Signs
 - Die Cast Aluminum Construction
 - Thin-Edge Black Housing
 - Brushed Aluminum Stencil Face
 - Directional Chevron Snapouts
 - UL Listed

Additional Emergency Unit Features

- 
 - Integrated Solid State System
 - Constant Current, Controlled Automatic Charger Circuit
 - Low-Voltage Battery Cutoff
 - Brownout Sensitivity
- 
 - Increased LED Brightness Level in Emergency Mode
- 
 - Sealed Nickel Cadmium Battery
 - 5-Year Shelf Life
 - 10-Year Battery Warranty
 - Maintenance-Free
- 
 - 3+ Hours Illumination in Emergency Mode
 - Test Switch
 - Red (Power On) Indicator

Ordering Information

DXLS Series	2 # Faces	R Letter Color	A Stencil Color	B Housing Color	-12 Options
DXLS – AC	1	R ed	W hite*	W hite*	Factory Options
EDXLS – Emer.	2	G reen	B lack	B lack	

*Standard