

# Die Cast Fluorescent Exits

**DXP**



DXP



EDXP

## Dimensions

### DXP/EDXP

Height: 8.3"  
Width: 13.3"  
Depth: 2.4"

### DXP CANOPY

Length: 4.7"  
Width: 4.7"  
Depth: 0.8"

### EDXP CANOPY

Length: 9.0"  
Width: 4.7"  
Depth: 2.3"

## Accessories Order Separately

**63** Wire Guard (for Single-Face, Back Mount DXP Only)














**VDS** Vandal-Deterrent Shield (for Single-Face, Back Mount DXP Only)

## Options















Add Suffix to Catalog Number

- 6** (2) 6VDC Lamps for AC/6VDC Remote Operation
- 12** (2) 12VDC Lamps for AC/12VDC Remote Operation
- 277** 277VAC Input
- 2CKT** (2) Independent AC Circuits
- CPY** Canopy (Single-Face DX)
- HPF** High Power Factor
- OF** Open-Face Panel (Fiber Std.)
- RMB** Recessed Mount Black (DXP Only)
- RMW** Recessed Mount White (DXP Only)
- TP** Tamper-Proof Screws

## Series Features

-  • 120VAC Operation Standard
-  • Maximum Input Rating (120 or 277VAC) 20 Watts
-  • Energy-Saving Compact Fluorescent
-  • (2) 120VAC, 7-Watt Lamps
-  • Ceiling, End or Back Mount
-  • Canopy Standard on Double-Face Sign
-  • Universal Stencil
-  • Directional Chevron Snapouts
-  • Prismatic Downlight Lens
-  • Die Cast Aluminum Housing
-  • Matte Black Frame
-  • Brushed Aluminum Stencil Face
-  • UL Listed

## Additional Emergency Unit Features

-  • Integrated Solid State System
-  • Constant Current, Automatic Charger
-  • Lock Out (Automatic Battery Connect)
-  • Low-Voltage Battery Cutoff
-  • Brownout Sensitivity
-  • Maximum Input Rating (120 or 277VAC) 22 Watts
-  • Long-Life Incandescent
-  • (2) 6VDC, 3-Watt Lamps
-  • Sealed Nickel Cadmium Battery
-  • 6-Volt Operation
-  • Maintenance-Free
-  • Canopy (with Electronics & Battery)
-  • Test Switch
-  • Red (Power On) Indicator

## Ordering Information

<b>2</b>	<b>DXP</b>	<b>1</b>	<b>G</b>	<b>A**</b>	<b>B</b>	<b>-12</b>
Fluorescent AC Lamps	Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
1	DXP - AC	1	R ed	W hite	W hite	Factory Options
2*	EDXP - Emer.	2	G reen	B lack	B lack*	
			W hite	A luminum*	P M Painted Matte Chrome	

\*Standard

\*\*Background Panel Color on Open-Face Signs



Made in USA