

## Series Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 0.35 Amps  
277VAC 60 Hz 0.15 Amps



- HIT Lamps
  - PAR-36 Sealed Beams
- STD Lamp: See Unit Information



- Sealed Lead Calcium Battery (S) or Sealed Nickel Cadmium Battery (N)
- 6 or 12 Volt Operation
- Maintenance-Free



- Contemporary 3-D Design
- 20-Gauge Steel Housing
- Polycarbonate Lamp Heads (Rectangular)
- Steel Lamp Heads (Round)
- Universal Mount Backplate
- Beige Powder-Coat Finish Standard
- Red (Power On) LED Indicator
- Test Switch
- UL Listed
- New York City Approved/Calendar #32110

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery	Head Shape
		1.5	2	3	4	5	6	7	8		
2ET6S5	6	12	9	6	-	-	-	-	-	(1) S65	Rect angl
2ET6S8	9	18	14	9	7	-	-	-	-	(1) S68	Rect angl
2ET6S8-8	8	18	14	9	7	-	-	-	-	(1) S68	Round
H2ET6S10†	12	32	24	16	12	10	8	7	6	(1) S610SL	Round
H2ET6S16†	12	36	27	18	14	11	9	8	7	(2) S68	Round
H2ET12S7†	12	36	27	18	14	11	9	8	7	(2) S68	Round
2ET6N7*	9	18	14	9	7	-	-	-	-	(1) N67F	Rect angl
2ET12N7*	9	36	28	18	14	11	9	8	7	(1) N127	Rect angl
H2ET6N7*	8	18	14	9	7	-	-	-	-	(1) N67F	Round
H2ET6N14*	8	36	28	18	14	11	9	8	7	(2) N67F	Round
H2ET12N7*	12	36	28	18	14	11	9	8	7	(1) N127	Round

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours.

NEC requires 1.5 hours of emergency illumination.

\*Meets or Exceeds UL 924 Requirements.

## Ordering Information

H	2	ET	6	S	10	-TD
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (S - Sealed) (N - Ni Cad)	Battery Amp/Hour	Options

# ET



Round Heads



Rectangular Heads

The ET Series is an ideal choice for commercial applications where ease of installation, reliability, and moderate remote loads are required.

## Dimensions

### ET

Height: 12.0"  
Width: 13.0"  
Depth: 3.0"

## Options

### Add Suffix to Catalog Number

- A Ammeter\*
  - BLK Black Finish
  - HMC Heads Mounted on Cover
  - HOS Heads Mounted on Sides
  - OW Designer Off-White Finish (Round Heads Only)
  - P2 Cord & Plug for 120VAC Input
  - QC Quik-Chek™ Remote Test & Time Delay
  - SD Self Diagnostic (See page 72)
  - TD Time Delay - Adjusts 1-60 min.
  - V Voltmeter\*
  - W White Finish
  - WG Wood Grain Front Panel
  - \*\* Special Lamp Wattage (See page 63)
- \*Choose Only One



Made in USA

