

ExceLite



Dimensions

EXCELITE

Height: 10.5"
Width: 6.5"
Depth: 3.8"

Options

Add Suffix to Catalog Number

-HTR Heater

The ExceLite is great for indoor or outdoor applications. A Ni-Cad battery allows for use in cold weather conditions. Decorative photocell operated LEDs make the ExceLite night time friendly.



Series Features



- Wet Location Emergency Light



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low Voltage Battery Cutoff
- Brownout Sensitivity
- Dual Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 - 120VAC 60 Hz 0.20 Amps
 - 277VAC 60 Hz 0.20 Amps



- 6 Watt Halogen Lamps
- Decorative Photocell LED Light



- Maintenance Free Ni-Cad Battery
- 6-Volt Operation
- Heater Option



- Innovative Architectural Design
- Die-cast Aluminum Housing
- Polycarbonate Lens/Mirrored Reflector
- Test Switch/Power Indicator Light
- Wet Location
- ETL Listed, Meets UL, NFPA, & OSHA

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour				Replacement Battery
		1.5	2	3	4	
ExceLite	6	12	-	-	-	(1) N65

Ordering Information

ExceLite	-HTR
Series	Factory Options