

## Series Features



- Integrated Solid State System and Switching
- Three-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Single-Voltage Transformer for 120VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 0.50 Amps  
277VAC 60 Hz 0.23 Amps



- PAR-46 Sealed Beam Lamps STD Lamp: See Unit Information



- Refillable Nickel Cadmium Battery
- -22°–140°F Operating Range
- 6-Volt Operation
- 20–25 Year Operating Life



- Rugged 20-Gauge Steel Housing
- Top End Battery Access
- Full-Length Piano Hinge with Lock Hasp
- Integral Carrying Handles
- Two-Tone Powder-Coat Finish (Beige & Cocoa) Standard
- Slide-Out Control Chassis
- Test Switch
- Battery Capacity Indicator: Incremental LED Panel Indicates Current Battery Charge/Discharge Status
- Amber (AC On) LED Indicator
- UL Listed

## GA



Shown in Standard Two-Tone Beige & Cocoa Finish

Rugged steel construction is combined with state-of-the-art LED status indicators, making the GA Series an ideal choice for demanding industrial applications. The Refillable Nickel Cadmium Battery provides 20 years of service in temperatures ranging from -22°F to 140°F.

### Dimensions

#### GA

Height: 20.5"  
Width: 18.5"  
Depth: 8.5"

### Options

#### Add Suffix to Catalog Number

- 277 277VAC Input
- BDS Battery Disconnect Switch
- GY Industrial Grey Finish
- P2 Cord & Plug for 120VAC Input
- QC Quik-Chek™ Remote Test & Time Delay
- TD Time Delay – Adjusts 1–60 min.
- ..\*\* Special Lamp Wattage (See page 63)

\*In Place of Ammeter

Order No. 22 Mounting Shelf

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2GA6N40†	25	100	75	50	32	28	24	20	16	(1) N640
2GA6N50†	25	120	85	55	40	34	28	24	20	(1) N650

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

## Ordering Information

H	2	GA	6	N	40	-QC
Halogen Lamp Prefix*	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (N – Ni Cad)	Battery Amp/Hour	Options

\*PAR-36 Sealed Beam

