

Industrial Emergency Lights

IQ



Dimensions

IQ
 Height: 17.25"
 Width: 15.75"
 Depth: 7.50"

Options

Add Suffix to Catalog Number

- BG** All Beige Finish
- GY** Industrial Grey Finish
- OW** Designer Off-White Finish
- P2** Cord & Plug for 120VAC Input
- V** Voltmeter*
- .**** Special Lamp Wattage (See page 63)

*In Place of Ammeter

Shown in Standard Two-Tone Beige & Cocoa Finish

The IQ Series is the perfect choice for light industrial facilities where aesthetics and performance are of principal consideration. Available with sealed or refillable batteries for use in a wide temperature range, the IQ is also equipped with Quik-Chek™, our exclusive remote testing feature for emergency lights.



Made in USA



Series Features

QUIK-CHEK™ REMOTE CONTROL TESTING*



- Verifies Operation of Lamps, Charger and Battery
- Hand-Held Transmitter – 1'-50' Range
- Field Adjustable Time Delay – 1-90 Minutes
- U.S. Patent #5148158, Canadian Patent #1320246




- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 120VAC 60 Hz 0.35 Amps
 277VAC 60 Hz 0.15 Amps



- PAR-36 Sealed Beam Lamps 6-Volt – 25-Watt
 12-Volt – 25-Watt



- Sealed Lead Calcium Battery (S)
- Refillable Lead Acid Battery (L)
- 6 or 12 Volt Operation



- Rugged 20-Gauge Steel Housing
- Front Battery Access
- Keyhole Mounting with Integral Shelf
- Two-Tone Powder-Coat Finish (Beige & Cocoa) Standard
- Red (Power On) & Green (Trickle Charge) LED Indicators
- Test Switch
- Ammeter
- Modular Control Chassis
- UL Listed
- New York City Approved/Calendar #38236

*See pages 69-70 for additional Quik-Chek™ information.

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2I Q6S20†	25	64	50	32	24	19	14	13	12	(2) S610SL
2I Q6S36†	25	100	75	50	38	30	25	21	18	(1) S636
2I Q6S50†	25	120	90	60	45	36	30	26	23	(1) S650
2I Q6L40†	25	120	90	60	45	36	30	26	23	(1) L640
2I Q12S10†	25	60	45	30	23	18	15	13	11	(2) S610SL
2I Q12S15†	25	100	75	50	38	30	25	21	18	(1) S1215
2I Q12S20†	25	120	90	60	45	36	30	26	23	(1) S1220
2I Q12S36†	25	200	150	100	76	50	50	42	36	(2) S636

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

H	2	IQ	6	S	50	-20
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage (6 – 6-Volt) (12 – 12-Volt)	Battery Type (S – Sealed) (L – Lead Acid)	Battery Amp/Hour	Options