

Series Features


- Integrated Solid State System
- Three-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Single-Voltage Transformer for 120VAC Operation
- Maximum Input Rating
120VAC 60 Hz 0.50 Amps
277VAC 60 Hz 0.23 Amps



- PAR-36 Sealed Beam Lamps STD Lamp: See Unit Information



- Sealed Lead Calcium Battery (S) or Refillable Lead Acid Battery (L)
- 6 or 12 Volt Operation
- Maintenance-Free (S Only)



- Rugged 20-Gauge Steel Housing
- Top End Battery Access
- Keyhole Mount Standard or Order Shelf No. 23
- Two-Tone Powder-Coat Finish (Beige & Cocoa) Standard
- Top or Side Lamp Mounting
- Test Switch
- Battery Capacity Indicator: Incremental LED Panel Indicates Current Battery Charge/Discharge Status
- Amber (AC On) LED Indicator
- UL Listed

Order No. 23 Mounting Shelf

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2LT6L40†	25	120	90	60	45	36	30	26	22	(1) L640
H2LT6L40†	20	120	90	60	45	36	30	26	22	(1) L640
2LT6S50†	25	120	90	60	45	36	30	26	22	(1) S650
H2LT6S50†	20	120	90	60	45	36	30	26	22	(1) S650
2LT12S20†	25	120	90	60	45	36	30	26	22	(1) S1220
H2LT12S20†	12	120	90	60	45	36	30	26	22	(1) S1220

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours.

NEC requires 1.5 hours of emergency illumination.

Ordering Information

H	2	LT	12	S	20	-QC
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage (6 - 6-Volt) (12 - 12-Volt)	Battery Type (S - Sealed) (L - Lead Acid)	Battery Amp/Hour	Options

LT



Shown in Standard Two-Tone Beige & Cocoa Finish

Dimensions

LT
Height: 16.5"
Width: 15.0"
Depth: 6.0"

Options

Add Suffix to Catalog Number

- 277 277VAC Input
- BDS Battery Disconnect Switch
- GY Industrial Grey Finish
- P2 Cord & Plug for 120VAC Input
- QC Quik-Chek™ Remote Test & Time Delay
- TD Time Delay - Adjusts 1-60 min.
- ** Special Lamp Wattage (See page 63)

The LT Series is equipped with an advanced LED battery capacity indicator, offering increased unit status information while the customized, three-rate charging circuit extends battery life.



Made in USA

