

Commercial Emergency Lights

MQ



Dimensions

MQ

Height: 15.4"
Width: 10.3"
Depth: 3.5"

Options

Add Suffix to Catalog Number

- BG Beige Finish
- BLK Black Finish
- P2 Cord & Plug for 120VAC Input
- V Voltmeter*
- W White Finish
- ** Special Lamp Wattage (See page 63)

*In Place of Ammeter

Shown in Optional White Finish

The MQ Series combines state-of-the-art unit performance with traditional wall-mount styling. Standard equipment includes Quik-Chek™, our exclusive remote testing feature for emergency lights.



Made in USA



Series Features

QUIK-CHEK™ REMOTE CONTROL TESTING*



- Verifies Operation of Lamps, Charger and Battery
- Hand-Held Transmitter – 1'-50' Range
- Field Adjustable Time Delay – 1-90 Minutes
- U.S. Patent #5148158, Canadian Patent #1320246




- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
120VAC 60 Hz 0.35 Amps
277VAC 60 Hz 0.15 Amps



- HIT Lamps
 - PAR-36 Sealed Beams
- STD Lamp: See Unit Information



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free



- Traditional Styling
- 20-Gauge Steel Housing
- Designer Off-White Powder-Coat Finish
- Keyhole Mount
- Red (Power On) LED Indicator
- Test Switch
- Ammeter
- UL Listed
- New York City Approved/Calendar #38236

*See pages 69-70 for additional Quik-Chek™ information.

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2MQ6S10	8	32	24	16	12	10	8	7	6	(1)
H2MQ6S10†	12	32	24	16	12	10	8	7	6	S610SL
H2MQ6S16†	12	36	27	18	14	11	9	8	7	(1)

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

H	2	MQ	6	S	10	-V
Halogen Lamp Prefix	Lamp Heads on Unit	Series	DC Battery Voltage	Battery Type (S - Sealed)	Battery Amp/Hour	Options