

NX



Dimensions

NX
 Height: 8.8"
 Width: 14.2"
 Depth: 1.2"
 (Single Face)
 Depth: 2.3"
 (Double Face)

Options

Add Suffix to Catalog Number

-AF Aluminum Frame
-IF Institutional Frame
-RM Recessed Mount






Accessories

Order Separately

63 Wire Guard (for Single-Face Back Mount Only)
P12NXW 12" Pendant Kit, White
P12NXB 12" Pendant Kit, Black
VDS Vandal-Deterrent Shield (for Single-Face Back Mount NX Only)



Series Features

-  • Requires No Electrical Supply
-  • Internally Illuminated Glass Tubes Coated with Zinc Phosphor and Tritium Gas
- Initial Brightness
 - 0.15 Foot Lamberts (10 Years)
 - 0.18 Foot Lamberts (15 Years)
 - 0.25 Foot Lamberts (20 Years)
- End-of-Life Brightness Exceeds Minimum Code Requirement of .06 Foot Lamberts
-  • Requires No Battery Supply
-  • 10-, 15- or 20-Year Illumination
- No Internal or External Wiring Required
- Completely Sealed
- Explosion Proof
- Waterproof
- Corrosion, Mold and Vapor Proof
- Operating Range: -60°–180°F
-  • High Impact, ABS Fire-Retardant Case
- LEXAN® Cover
- Ceiling, End or Back Mount
- Universal Chevron Configuration
- Mist White Finish
- Complies with NFPA Life Safety Code, NRC, OSHA and Council of American Building Officials
- UL Listed

Ordering Information

2	NX	10	R	W	-RM
# Faces	Series	Sign Life	Stencil Color	Housing Color	Options
1 2		10 Years 15 Years 20 Years	Red Green Black	White* Black Grey	Factory Options

*Standard