

Commercial Emergency Lights

SC



Dimensions

SC
 Height: 13.5"
 Width: 13.5"
 Depth: 4.75"

Options

Add Suffix to Catalog Number

- GY** Industrial Grey Finish
- NWG** Less Wood Grain
- OW** Designer Off-White Finish
- P2** Cord & Plug for 120VAC Input
- QC** Quik-Chek™ Remote Test & Time Delay
- TD** Time Delay – Adjusts 1–60 min.
- V** Voltmeter*
- W** White Finish
- .**** Special Lamp Wattage (See page 63)

*In Place of Ammeter

Shown in Standard Beige Finish with Wood Grain Panel

The SC Series is a high-end commercial unit, offering the appealing blend of durable steel construction with an attractive, neat appearance. Enhanced unit status information is provided through indicator and meter displays.



Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Fused AC Input & DC Output Circuit Protection
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 120VAC 60 Hz 0.35 Amps
 277VAC 60 Hz 0.15 Amps
- HIT Lamps
- PAR-36 Sealed Beams
- Sealed Lead Calcium Battery (S) or Sealed Nickel Cadmium Battery (N)
- 6 or 12 Volt Operation
- Maintenance-Free
- Rugged 20-Gauge Steel Housing
- Top End Battery Access
- Full-Length Piano Hinge
- Keyhole Mounting or Order No.19B Shelf
- Beige Powder-Coat Finish Standard
- Wood Grain Panel Design
- Ammeter
- Red (Power On) & Green (Trickle Charge) LED Indicators
- Test Switch
- UL Listed
- New York City Approved/Calendar #32110
- Voltmeter for Nickel Cadmium Units

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2SC6S8	8	18	14	9	7	-	-	-	-	(1) S68
2SC6S10	8	32	24	16	12	10	8	7	6	(1) S610SL
2SC6S16	8	36	27	18	14	9	8	7	-	(2) S68
2SC6S20	8	64	50	32	24	19	16	14	12	(2) S610SL
2SC6S36	8	100	75	50	38	30	25	21	18	(1) S636
H2SC6S10†	12	32	24	16	12	10	8	7	6	(1) S610SL
H2SC6S16†	12	36	27	18	14	11	9	8	7	(1) S68
H2SC6S20†	12	64	50	32	24	19	16	14	12	(2) S610SL
H2SC6S36†	12	100	75	50	38	30	25	21	18	(1) S5636
H2SC12S7†	12	36	27	18	14	11	9	8	7	(2) S68
H2SC12S10†	12	60	45	30	23	18	15	13	11	(2) S610SL
H2SC12S15†	12	100	75	50	38	30	25	21	18	(1) S1215
2SC6N7*	8	18	14	9	7	-	-	-	-	(1) N67F
2SC12N7*	18	36	28	18	14	11	9	8	7	(1) N127
H2SC6N7*	8	18	14	9	7	-	-	-	-	(1) N67F
H2SC12N7*	12	36	28	18	14	11	9	8	7	(1) N127
H2SC6N14*	8	36	28	18	14	11	9	8	7	(2) N67F
H2SC12N7*	12	36	28	18	14	11	9	8	7	(1) N127

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

*Meets or Exceeds UL 924 Requirements.

Ordering Information

H	2	SC	12	S	10	-P2
Halogen Lamp Prefix	Lamp Heads on Unit (1,2,3)	Series	DC Battery Voltage	Battery Type (S – Sealed (N – Ni Cad)	Battery Amp/Hour	Options