

Series Features



NEMA APPLICATIONS

- All Units Satisfy the Requirements of NEMA 1, 2, 3, 3R, 4, 4X, 12 & 13 Enclosures



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger No Manual Battery Recycling
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating

120VAC	60 Hz	0.35 Amps
277VAC	60 Hz	0.15 Amps



- PAR-36 Sealed Beam Lamps STD Lamp: See Unit Information



- Sealed Lead Calcium Battery (S) or Sealed Nickel Cadmium Battery (N)
- 6 or 12 Volt Operation
- Maintenance-Free



- NEMA-Rated Enclosure for Corrosive, Dirty or Damp Environments
- Lite Grey Fiberglass Housing
- Polycarbonate Lamp Enclosures
- Hinged Front Panel with Locking Hasp
- Easy Battery Access
- Side-Mounted Test Switch
- Red (Power On & Charge) LED Indicator
- Meets or Exceeds UL 924

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
8				9	7	-		-	-	
8							8	7	6	
8							9	8	7	
8										
8										
8										
8							9	8	7	
8										
8				9	7	-	-	-	-	
8				9	7	-	-	-	-	
8							9	8	7	
8							9	8	7	

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

H	2	SE	12	S	7	-QC
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2)	Series	DC Battery Voltage (6 - 6-Volt) (12 - 12-Volt)	Battery Type (S - Sealed) (N - Ni Cad)	Battery Amp/Hour	Options

SE



Constructed of industrial-grade fiberglass, the SE Series is the only choice for severe or corrosive applications. All units satisfy the requirements of NEMA 1, 2, 3, 3R, 4, 4X, 12 & 13 Environments.

Dimensions

- 2SE6S8
- 2SE6S10
- 2SE6S16
- 2SE6S20
- 2SE6S36
- 2SE6S50
- H2SE12S7
- H2SE12S10
- 2SE6N7
- 2SE12N7
- H2SE6N7
- H2SE12N7

Height: 16.9"
Width: 9.4"
Depth: 5.5"

H2SE12S20
Height: 18.8"
Width: 11.4"
Depth: 5.6"

2SE6S72DO
H2SE12S36
Height: 20.6"
Width: 13.5"
Depth: 7.0"

Options

Add Suffix to Catalog Number

- FSH** Food-Safe Heads (Lexan Lens Guards)
- HTR** Heater
- QC** Quik-Chek™ Remote Test & Time Delay
- SD** Self Diagnostic
- TD** Time Delay - Adjusts 1-60 min.
- .**** Special Lamp Wattage (See page 63)



Made in USA

