



ESDX

Dimensions

STANDARD

Height: 7.5"
Width: 18.0"
Depth: 2.0"

NEW YORK CITY

Height: 11.0"
Width: 14.5"
Depth: 2.3"

Options

Add Suffix to Catalog Number

- DMP** Damp Location Listing (Damp Label)
- NY** New York City Approved with 8" Letters
- REC** Recessed Housing (Single-Face Only)
- TP** Tamper-Proof Screws
- U** Universal Face (Additional Backplate – Double-Face Signs Only)





Accessories

Order Separately

- 63** Wire Guard (for Single-Face Back Mount Only)
 - P12** 12" Pendant Kit, White*
 - P12B** 12" Pendant Kit, Black*
- *Pendant Kits from 12" to 84" Available
- VDS** Vandal-Deterrent Shield (for Single-Face Back Mount Only)



Series Features

- 
 - 120/277 VAC Operation
 - Maximum Input Rating (120 or 277VAC) Standard 1.7 Watts
 - Integrated Solid State System
 - Constant Current, Controlled Automatic Charger Circuit
 - Low-Voltage Battery Cutoff
 - Brownout Sensitivity
- 
 - Light-Emitting Diodes – 25+ Year Life
 - Illuminates with Uniform Color and Brightness
 - Indirect Placement for Diffused Legend Output
 - Increased LED Brightness Level in Emergency Mode
- 
 - Sealed Nickel Cadmium Battery
 - 5-Year Shelf Life
 - 10-Year Battery Warranty
 - Maintenance-Free
- 
 - Ceiling, End or Back Mount
 - Canopy
 - Universal Stencil
 - Directional Chevron Snapouts
 - 20-Gauge Steel Housing
 - White Powder-Coat Finish
 - Easy Installation
 - UL Listed
 - 3+ Hours Illumination in Emergency Mode*
 - Test Switch
 - LED (Power On) Indicator

*Longer Illumination Times Available. Consult Factory.

Ordering Information

ESDX	2	R	W	W	-U
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
	1 2	R ed G reen	W hite* B lack M atte Chrome	W hite* B lack M atte Chrome	Factory Options

*Standard