

ESDX



Series Features

- Standard Self Diagnostic Feature (see page 72)
- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC) Standard 1.7 Watts
- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity



- Light-Emitting Diodes — 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Increased LED Brightness Level in Emergency Mode



- Sealed Nickel Cadmium Battery
- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free



- Ceiling or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- Easy Installation
- UL Listed
- 3+ Hours Illumination in Emergency Mode*
- Test Switch
- LED (Power On) Indicator

*Longer Illumination Times Available. Consult Factory.

Accessories

Order Separately

63 Wire Guard (for Single-Face Back Mount Only)

P12W 12" Pendant Kit, White*

P12B 12" Pendant Kit, Black*
*Pendant Kits from 12" to 84" Available

VDS Vandal-Deterrent Shield (for Single-Face Back Mount Only)

Dimensions

STANDARD

Height: 7.5"
Width: 18.0"
Depth: 2.0"

Options

Add Suffix to Catalog Number

-DMP Damp Location Listing (Damp Label)

-TP Tamper-Proof Screws

-U Universal Face (Additional Backplate — Double-Face Signs Only)

Ordering Information

ESDX	2	R	W	W	-U
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
	1	Red	White*	White*	Factory
	2	Green	Black	Black	Options
			PM Painted	PM Painted	
			Matte Chrome	Matte Chrome	

See page 72 for SD Information.

*Standard



Made in USA