



Dimensions

VRX / EVRX

Height: 8.5"
Width: 13.0"
Depth: 3.25"

VRX/EVRX

Options

Add Suffix to Catalog Number

-2CKT (2) Independent AC Circuits (VRXL Only)

-BZ Audible Buzzer in Emergency Mode (EVRXD Only)

-DL Downlight LED (VRXD/EVRXD Only)

-DMP Damp Location Listing (Damp Label)

-DS Double LED Strip (VRXL/EVRXL Only)

-FAI Fire Alarm Interface

-FL Flasher in Emergency Mode (EVRXD Only)

-HI High-Intensity LEDs

-HTR Heater

Series Features



- 120/277 VAC Input
- Light-Emitting Diodes
- Illuminates with Uniform Color and Brightness
- Directly Viewed LEDs have 100–300 Foot Visibility
- 25+ Year Life (No Relamping)



- Rugged 16-Gauge Housing
- Polycarbonate Face Shield
- Tamper-Proof Screws
- Canopy Factory Attached (Specify Location)
- White Powder-Coat Finish
- Meets or Exceeds UL Standards

Additional Emergency Unit Features



- Integrated Solid State System
- Constant Current, Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- AC Lockout (Line Latching)



- Sealed Nickel Cadmium Battery
- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free



- Increased Illumination During Power Failure
- Test Switch
- Power On Indicator LED Lamp

Diffused LED Rating



- Maximum Input Rating (120 or 277VAC)

Standard	1.7 Watts
DS Option	3.5 Watts
- 3+ Hours Illumination in Emergency Mode

Direct View LED Rating



- Maximum Input Rating (120 or 277VAC)

AC Only	Single Face	3.6 Watts
	Double Face	5.6 Watts
Emergency	Single Face	6.8 Watts
	Double Face	8.0 Watts
- 3+ Hours Illumination in Emergency Mode (Single)
- 1.5 Hours Illumination in Emergency Mode (Double)

Ordering Information



EVRX Series	L LED Type	1 # Faces	R Letter Color	W Stencil Color	W Housing Color	-DMP Options
VRX – AC Only	L – Diffused	1	R ed	W hite	W hite	Factory Options
EVRX – Emer.	D – Direct View	2	G reen	B lack	B lack	