

Series Features

- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC)
 - Single Face 3.6 Watts
 - Double Face 5.6 Watts
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- 100–300 Foot Visibility
- Ceiling, End or Back Mount
- Canopy
- 20-Gauge Steel Housing
- Acrylic Shield
- White Powder-Coat Finish
- Universal Directional Chevrons
- UL Listed

Additional Emergency Unit Features

- Maximum Input Rating (120 or 277VAC)
 - Single Face 6.8 Watts
 - Double Face 8.0 Watts
- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Voltage Surge Protection
- Sealed Nickel Cadmium Battery
- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free
- 3+ Hours Illumination (Single Face) in DC Mode
- 1.5+ Hours Illumination (Double Face) in DC Mode
- Test Switch
- Amber (AC On/Charger Operation) Indicator

Ordering Information

EXFLD	2	R	W	W	-FAI
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
XFLD – AC EXFLD – Emer.	1 2	R ed G reen	W hite* B lack PM Painted Matte Chrome	W hite* B lack PM Painted Matte Chrome	Factory Options

XFLD



Accessories Order Separately

- 63** Wire Guard (for Single-Face Back Mount Only)
 - P12W** 12" Pendant Kit, White*
 - P12B** 12" Pendant Kit, Black*
 - VDS** Vandal-Deterrent Shield (for Single-Face Back Mount Only)
- *Pendant Kits from 12" to 84" Available

Dimensions

XFLD/EXFLD
Height: 7.7"
Width: 12.5"
Depth: 2.7"

Options

- Add Suffix to Catalog Number**
- BZ** Audible Buzzer in Emergency Mode (EXFLD Only)
 - FAI** Fire Alarm Interface
 - FL** Flasher in Emergency Mode (EXFLD Only)
 - HI** High-Intensity LEDs
 - REC** Recessed Housing (Single Face Only)
 - TP** Tamper-Proof Screws
- Master/Slave Options:**
- SL** Slave (Requires Single-Face EXFLD as Power Source)
 - REC/S** Recessed Mounting for Slave Only
 - REC/M** Recessed Mounting for Master Only
 - REC/MS** Recessed Mounting for Master and Slave



Made in USA