

Series Features



- 120VAC Operation Standard
- Maximum Input Rating
120VAC 20 Watts
277VAC 30 Watts



- Energy-Saving Compact Fluorescent
- (2) 120VAC, 7-Watt Lamps



- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- Downlight
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- UL Listed

Additional Emergency Unit Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Single-Voltage Transformer for 120VAC Operation
- Maximum Input Rating
(120 or 277VAC) 25 Watts



- Long-Life Incandescent
- (2) 6 VDC, 6-Watt Lamps



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free



- Test Switch
- Red (Power On) Indicator

Ordering Information

2	EXP	1	G	PM**	B	-U
# Fluorescent AC Lamps 1 2*	Series XP - AC EXP - Emer.	# Faces 1 2	Letter Color B ed G reen W hite	Stencil Color W hite* B lack PM Painted Matte Chrome	Housing Color W hite* B lack PM Painted Matte Chrome	Options Factory Options

*Standard

**Background Panel Color on Open-Face Signs

XP



Accessories

Order Separately

63 Wire Guard (for Single-Face Back Mount Only)

P12W 12" Pendant Kit, White*

P12B 12" Pendant Kit, Black*

*Pendant Kits from 12" to 84" Available

VDS Vandal-Deterrent Shield (for Single-Face Back Mount XP Only)

Dimensions

XP

Height: 7.5"
Width: 12.3"
Depth: 2.0"

EXP

Height: 10.5"
Width: 12.3"
Depth: 2.0"

Options

Add Suffix to Catalog Number

-6 (2) 6VDC Lamps for AC/6VDC Remote Operation

-12 (2) 12VDC Lamps for AC/12VDC Remote Operation

-277 277VAC Input

-2CKT (2) Independent AC Circuits

-OF Open-Face Panel (Fiber Std.)

-REC Recessed Housing (Single-Face XP Only)

-TP Tamper-Proof Screws

-U Universal Face (Additional Backplate - Double-Face Signs Only)



Made in USA