



XP



EXP

Options
Add Suffix to Catalog Number

- 6** (2) 6VDC Lamps for AC/6VDC Remote Operation
- 12** (2) 12VDC Lamps for AC/12VDC Remote Operation
- 277** 277VAC Input
- 2CKT** (2) Independent AC Circuits
- OF** Open-Face Panel (Fiber Std.)
- REC** Recessed Housing (Single-Face XP Only)
- TP** Tamper-Proof Screws
- U** Universal Face (Additional Backplate – Double-Face Signs Only)

Dimensions

- XP**
Height: 7.5"
Width: 12.3"
Depth: 2.0"
- EXP**
Height: 10.5"
Width: 12.3"
Depth: 2.0"

Accessories
Order Separately

- 63** Wire Guard (for Single-Face Back Mount Only)
- P12** 12" Pendant Kit, White*
- P12B** 12" Pendant Kit, Black*
- *Pendant Kits from 12" to 84" Available
- VDS** Vandal-Deterrent Shield (for Single-Face Back Mount XP Only)



Series Features

- 120VAC Operation Standard
- Maximum Input Rating
120VAC 20 Watts
277VAC 30 Watts
- Energy-Saving Compact Fluorescent
- (2) 120VAC, 7-Watt Lamps
- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- Downlight
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- UL Listed

Additional Emergency Unit Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Single-Voltage Transformer for 120VAC Operation
- Maximum Input Rating
(120 or 277VAC) 25 Watts
- Long-Life Incandescent
- (2) 6 VDC, 6-Watt Lamps
- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free
- Test Switch
- Red (Power On) Indicator

Ordering Information

2	XP	1	G	M**	B	-U
# Fluorescent AC Lamps	Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
1	XP – AC	1	R ed G reen W hite	W hite* B lack M atte Chrome	W hite* B lack M atte Chrome	Factory Options
2*	EXP – Emer.	2				

*Standard

**Background Panel Color on Open-Face Signs