

Industrial Emergency Lights

AR



Dimensions

AR

Height: 16.0"
Width: 14.3"
Depth: 5.9"

Options

Add Suffix to Catalog Number

- GY** Industrial Grey Finish
- P2** Cord & Plug for 120VAC Input
- QC** Quik-Chek™ Remote Test & Time Delay
- TD** Time Delay – Adjusts 1–60 min.
- .**** Special Lamp Wattage (See page 63)

Shown in Standard Beige Finish


The AR Series is equipped with a refillable lead acid battery, providing 8 to 12 years of service in ambient temperatures ranging from 32°F to 105°F.






Made in USA



Series Features

- 
 - Integrated Solid State System
 - Multi-Rate, Controlled, Automatic Charger
 - Fused AC Input & DC Output Circuit Protection
 - Low-Voltage Battery Cutoff
 - Brownout Sensitivity
 - Dual-Voltage Transformer for 120/277 VAC Operation
 - Maximum Input Rating

120VAC	60 Hz	0.35 Amps
277VAC	60 Hz	0.15 Amps
- 
 - PAR-36 Sealed Beam Lamps, STD Lamp: See Unit Information
- 
 - Refillable Lead Acid Battery
 - 32°–105°F Operating Range
 - 6-Volt Operation
 - 8–12 Year Operating Life
- 
 - Rugged 20-Gauge Steel Housing
 - Top End Battery Access
 - Keyhole Mount Standard or Order Shelf No. 23
 - Beige Powder-Coat Finish Standard
 - Test Switch
 - Red (Power On) & Green (Trickle Charge) LED Indicators
 - UL Listed

Order No. 23 Mounting Shelf

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2AR6L40†	25	120	90	60	45	36	30	26	23	(1) L640
H2AR6L40†	20	120	90	60	45	36	30	26	23	(1) L640

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

H	2	AR	6	L	40	-P2
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (L – Lead Acid)	Battery Amp/Hour	Options