

Series Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
120VAC 60 Hz 0.35 Amps
277VAC 60 Hz 0.15 Amps



- PAR-36 Sealed Beam Lamps STD Lamp: See Unit Information



- Sealed Lead Calcium Battery (S), Refillable Lead Acid Battery (L) or Sealed Nickel Cadmium Battery (N)
- 6, 12, or 24 Volt Operation
- Maintenance-Free (S and N only)



- Rugged 20-Gauge Steel Housing
- Front Battery Access
- Keyhole Mounting with Integral Shelf
- Two-Tone Powder-Coat Finish (Beige & Cocoa) Standard
- Red (Power On) & Green (Trickle Charge) LED Indicators
- Test Switch
- Ammeter
- Modular Control Chassis
- UL Listed
- New York City Approved/Calendar #38236
- Voltmeter for Nickel Cadmium Units

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour				Replacement Battery
		1.5	2	4	8	
2I L6S20†	25	64	50	24	12	(2) S610SL
2I L6S36†	25	100	75	38	18	(1) S636
2I L6S50†	25	120	90	45	23	(1) S650
2I L12S10†	25	60	45	23	11	(2) S610SL
2I L12S15†	25	10	75	38	18	(1) S1215
2I L12S20†	25	120	90	45	23	(1) S1220
2I L12S36†	25	200	150	76	36	(2) S636
2I L24S10-	7	110	84	42	21	(4) S610SL
2I L24S15-	7	220	165	83	42	(2) S1215
2I L6L40†	25	120	90	45	23	(1) L640
2I L6N14*	18	36	28	14	7	(2) N67F
2I L6N21*	25	54	42	21	10	(3) N67F
2I L6N28*	25	72	56	28	14	(4) N67F
2I L12N7*	18	36	28	14	7	(1) N127
2I L12N14*	25	72	56	28	14	(2) N127
2I L12N21*	25	108	84	42	21	(3) N127
2I L12N28*	25	144	112	56	28	(4) N127

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

*Meets or Exceeds UL 924 Requirements.

Ordering Information

H	2	IL	12	S	36	-12
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage (6 - 6-Volt) (12 - 12-Volt) (24 - 24-Volt)	Battery Type (S - Sealed) (N - Ni Cad) (L - Lead Acid)	Battery Amp/Hour	Options

IL



Shown in Standard Two-Tone Beige & Cocoa Finish

Dimensions

IL
Height: 17.25"
Width: 15.75"
Depth: 7.50"

Options

Add Suffix to Catalog Number

- BG All Beige Finish
- GY Industrial Grey Finish
- OW Designer Off-White Finish
- P2 Cord & Plug for 120VAC Input
- TD Time Delay - Adjusts 1-60 min.
- V Voltmeter*
- ** Special Lamp Wattage (See page 63)

*In Place of Ammeter

Streamlined product design makes the IL Series the perfect choice for light industrial applications where aesthetics are of principal consideration. Available with sealed or refillable batteries for use in a wide temperature range.



Made in USA