

## Series Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 0.20 Amps  
277VAC 60 Hz 0.20 Amps



- High Intensity Tungsten Lamps, 9-Watt



- Sealed Lead Calcium Battery
- 6 or 12 Volt Operation
- Maintenance Free



- Compact Design
- Injection Molded Polycarbonate Housing
- High Impact, White Finish
- Red (Power On) LED Indicator Light
- Test Switch
- Damp Location
- UL 924 Listed

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour				Replacement Battery
		1.5	2	3	4	
2RC6S20	9	54	48	32	24	(2) S610SL
2RC12S10	9	54	48	32	24	(2) S610SL

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

## Ordering Information

2	RC	6	S	20
Lamp Heads on Unit	Series	DC Battery Voltage	Battery Type (S - Sealed)	Battery Type Amp/Hour

## RC



The RC series features a polycarbonate housing in the BBEM-6 family. The RC is great for applications where remotes or extended battery time is needed.

### Dimensions

**RC**  
Height: 7.5"  
Width: 14.75"  
Depth: 6.75"

