

Series Features



- Integrated Solid State System and Switching
- Three-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Single-Voltage Transformer for 120VAC Operation
- Maximum Input Rating
120VAC 60 Hz 1.0 Amps



- PAR-46 Sealed Beam Lamps, 6-Volt – 21-Watt



- Dry-Charged, Refillable Lead Acid Battery
- 32°–105°F Operating Range
- 6-Volt Operation
- 8–12 Year Operating Life



- Rugged 20-Gauge Steel Housing
- Top End Battery Access
- Battery Viewport
- Full-Length Piano Hinge with Lock Hasp
- Integral Carrying Handles
- Two-Tone Powder-Coat Finish (Beige & Cocoa) Standard
- Slide-Out Control Chassis
- Test Switch
- Load Cutoff Switch
- Voltmeter
- Amber (Power On), Red (Hi-Charge) and Green (Trickle Charge) Indicators
- UL Listed

Order No. 22 Mounting Shelf

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2SH6L40	21	120	90	60	45	36	30	26	23	(1) L640
2SH6L100	21	120	120	120	120	105	90	75	60	(1) L6100

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

2	SH	6	L	100	-P2
Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (L – Lead Acid)	Battery Amp/Hour	Options

SHL



Shown in Standard Two-Tone Beige & Cocoa Finish

Dimensions

SHL

Height: 20.5"
Width: 18.5"
Depth: 8.5"

Options

Add Suffix to Catalog Number

- GY Industrial Grey Finish
- P2 Cord & Plug for 120VAC Input

The SHL Series is equipped with solid state electronics and switching circuitry, which reduces component wear and dramatically extends product life. PAR-46 size lamps increase area illumination coverage.



Made in USA