

Series Features



- Integrated Solid State System and Switching
- Three-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Single-Voltage Transformer for 120VAC Operation
- Maximum Input Rating
120VAC 60 Hz 0.50 Amps
277VAC 60 Hz 0.23 Amps



- PAR-46 Sealed Beam Lamps* * See Unit Information



- Sealed Lead Acid AGM Battery
- 12 Volt Operation
- Maintenance-Free
- Operating Temperature Range (-40°F to +122°F)
- Unparalleled Deep Discharge Recovery
- AGM Separators Resist Oxidation & Retain Electrolyte



- Rugged 20-Gauge Steel Housing
- Top End Battery Access
- Full-Length Piano Hinge with Lock Hasp
- Integral Carrying Handles
- Two-Tone Powder-Coat Finish (Beige & Cocoa) Standard
- Slide-Out Control Chassis
- Test Switch
- Battery Capacity Indicator: Incremental LED Panel Indicates Current Battery Charge/Discharge Status
- Amber (Power On) LED Indicator
- UL Listed

Order No. 22 Mounting Shelf

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour							Replacement Battery
		1.5	2	4	8	16	20	24	
L2TC12SAGM40	3.8	120	90	45	23	12	9	8	(1)

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

L	2	TC	12	SAGM	40	-BDS
LED Lamp Prefix*	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage (12 - 12-Volt)	Battery Type (SAGM - Sealed Lead AGM)	Battery Amp/Hour	Options

TCSAGM



Shown in Standard Two-Tone Beige & Cocoa Finish

Rugged steel construction is combined with state-of-the-art LED status indicators, making the TCSAGM an ideal choice for demanding industrial applications. A slide-out modular control assembly allows for quick and easy product upgrades.

Dimensions

TCSAGM

Height: 20.5"
Width: 18.5"
Depth: 8.5"

Options

Add Suffix to Catalog Number

- 277** 277VAC Input
- BDS** Battery Disconnect Switch
- GY** Industrial Grey Finish
- P2** Cord & Plug for 120VAC Input
- QC** Quik-Chek™ Remote Test & Time Delay
- TD** Time Delay – Adjusts 1–60 min.



Made in USA

