

Commercial Emergency Lights

COB



Dimensions

COB

Height: 4.75"
Width: 9.0"
Depth: 2.75"

Options

Add Suffix to Catalog Number

-SD Self Diagnostic
-RC Remote Capable
-WL Wet Location Cover



Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
120VAC 60 Hz
277VAC 60 Hz
- Fully Adjustable, Glare Free, LED Lamp Heads
- High Output LED Model Available
- Sealed Nickel-Cadmium Battery
- Remote Capable Models Available w/ Nickel Metal Hydride Battery
- Maintenance-Free
- Injection-Molded Thermoplastic Housing
- Snap-Together Design for Fast Installation
- Fully Adjustable Lighting Heads
- White Finish
- Wall or Ceiling Mount
- LED Charge Rate Indicator
- Test Switch
- Damp Location Suitable
- UL Listed, CEC Registered

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

Ordering Information

2	COB	W	H	-SD
Lamp Heads on Unit	Series	Finish (W – White) (B – Black)	Lamp Output (Blank – Std) (H – High Output)	Options