

2ESDX



2ESDX-PH
Rectangular Heads



2ESDX
Round Heads

Dimensions

HOUSING

Height: 13.3"
Width: 12.3"
Depth: 2.3"
(Add 12.5" to the Overall Width Dimension for Round-Head Models)

Options

Add Suffix to Catalog Number

- U Universal Face (Additional Backplate — Double-Face Signs Only)



Made in USA

Series Features

- Standard Self Diagnostic Feature (see page 72)
- Dual-Voltage Transformer for 120/277 VAC Operation
- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Maximum Input Rating (120 or 277VAC) — 36 Watts



EMERGENCY LIGHT

- (2) 6VDC, 6-Watt HIT Lamps (PH)
- (2) 6VDC, 8-Watt PAR-36 Sealed Beams
- (2) PAR36 LED Sealed Beam, 5-Watt
- (2) Wedge Base LED Bulb, 1.5-Watt



EMERGENCY EXIT

- 2ESDX — LED (Indirect) 25+ Years
- (1) Strip, 120/277 VAC, 3.6-Watt



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free Battery

- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- Downlight (All Except ETXFL & ETXFLD)
- 20-Gauge Steel Housing
- Polycarbonate Lamp Enclosures (-PH)
- White Powder-Coat Finish
- Test Switch
- Red (Power On) & Green (Trickle Charge) LED Indicators
- UL Listed



Unit Information

Model Number	Watts per Hour								Replacement Battery
	1.5	2	3	4	5	6	7	8	
2ESDX	32	24	16	12	10	8	7	6	(1) S610SL

Ordering Information

LS	2	2ESDX	1	R	W†	W	-PH	-QC
LS-LED* L-LED 1.5W LPH-LED 1.5W	Emergency Light	Series ESDX	# Faces	Letter Color	Stencil Color	Housing Color	Head Type	Options
	0		1	Red Green White	White Black PM Painted Matte Chrome	White Black PM Painted Matte Chrome	Blank - Rnd. PH - Plastic Head	Factory Options
	1		2					
	2							

*Not Available on PH