



# Commercial Emergency Lights


BR



All Models



2BR6S8  
H2BR6S10  
2BR6S16



2BR6S20  
2BR6S36  
H2BR12S7  
H2BR12S10  
H2BR12S15

## Options

Add Suffix to Catalog Number

- BDS Battery Disconnect Switch
- BLK Black Finish
- OW Designer Off-White Finish
- PA Plenum Construction
- SD\* Self Diagnostic (See page 72)
- OW Designer Off White Finish (Round Heads Only)
- TD Time Delay-Adjusts 1-60 Min.
- \*\* Special Lamp Wattage (See page 63)

Shown in Standard White Finish

Providing a clean look in commercial installations, the BR Series combines the advantage of a fully recessed unit with maximum remote head capability.



Made in USA

## Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Fused AC Input & DC Output Circuit Protection
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 

120VAC	60 Hz	0.35 Amps
277VAC	60 Hz	0.15 Amps

- HIT Lamps STD Lamp: See Unit Information
- PAR-36 Sealed Beams Opt. PAR-36LED Sealed Beams 5W

- Sealed Lead Calcium Battery (S)
- 6 or 12 Volt Operation
- Maintenance-Free

- Fully Recessed Styling
- Designed for Use in 2-Foot Grid (T-Bar) Drop Ceilings
- Easy Access Battery Panels
- 20-Gauge Steel Housing
- Unit Mounts Up to 4 Lamp Heads
- White Powder-Coat Finish
- Red (Power On) LED Indicator
- Test Switch
- UL Listed
- New York City Approved/Calendar #38236

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2BR6S8†	8	18	14	9	7	-	-	-	-	(1) S68
H2BR6S10†	12	32	24	16	12	10	8	7	6	(1) S610SL
2BR6S16†	8	36	27	18	14	11	9	8	7	(2) S68
2BR6S20†	8	64	50	32	24	19	16	14	12	(2) S610SL
2BR6S36†	8	100	75	50	38	30	25	21	18	(1) S636
H2BR12S7†	12	36	27	18	14	11	9	8	7	(2) S68
H2BR12S10†	12	60	45	36	23	18	15	13	11	(2) S610SL
H2BR12S15†	12	100	75	50	38	30	25	21	18	(1) S1215

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours. NEC requires 1.5 hours of emergency illumination.

## Ordering Information

LS	2	BR	12	S	15	-PA
LS-LED H-Halogen	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (S - Sealed)	Battery Amp/Hour	Options

\*(not available on 2BR6S20 and 2BR6S36)