

CHL



CHL / ECHL

### Dimensions

CHL / ECHL  
 Height: 9.5"  
 Width: 12.3"  
 Depth: 2.0"

### Options




Add Suffix to Catalog Number

- TP Tamper-Proof Screws
- STAIR "STAIR" Legend in Lieu of "EXIT"
- STAIRS "STAIRS" Legend in Lieu of "EXIT"





### Accessories

- Order Separately
- 63 Wire Guard (for Single-Face Back Mount Only)
  - P12W 12" Pendant Kit, White\*

### Series Features

-  • 120/277 VAC Operation
-  • Maximum Input Rating (120 or 277VAC) Standard 1.7 Watts
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Ceiling, End or Back Mount
- Canopy
- Open-Face Glass Panel
- Silk Screen Letters
-  • 20-Gauge Steel Housing
- White Powder-Coat Finish
- Chicago Code Approved
- UL Listed

### Additional Emergency Unit Features





-  • Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
-  • Increased LED Brightness Level in Emergency Mode
-  • Sealed Nickel Cadmium Battery
- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free
-  • 3+ Hours Illumination in Emergency Mode\*
- Test Switch
- LED (Power On) Indicator

\*Longer Illumination Times Available. Consult Factory.



Made in USA

### Specify Arrow Configuration on all Open-Face Signs

- Blank = No Arrow
- AR = Arrow Right 
- AL = Arrow Left 
- DA = Dual Arrow 
- ARAL = Arrow Right/Arrow Left (Double-Face Only – 1 Arrow per Face) 

### Ordering Information

CHL	1	R	W	W	-TP
CHL-AC Only ECHL – Emer.	# Faces 1 2	Letter Color Red	Panel Color White	Housing Color White* Black PM Painted Matte Chrome	Option Factory Options