

# Commercial Emergency Lights

CL



Shown with Plastic Heads



Round Heads

Shown in Standard Designer Off-White Finish (Round Heads Only)

## Dimensions

### STANDARD HEADS

Height: 13.8"  
Width: 10.3"  
Depth: 3.5"

### ROUND HEADS

Height: 15.4"  
Width: 11.7"  
Depth: 3.8"

## Options

Add Suffix to Catalog Number

- BC Beige & Cocoa Two-Tone Finish
- BG Beige Finish
- BLK Black Finish
- P2 Cord & Plug for 120VAC Input
- TD\* Time Delay – Adjusts 1–60 min.
- W White Finish
- \*\* Special Lamp Wattage (See page 63)

\*(Not available on 2CL6S36 and 2CL12S15)

Maximizing remote head performance in a low-cost, traditionally styled fixture, the CL Series is capable of powering up to 100 watts in remote lamp loads.



Made in USA

## Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 

120VAC	60 Hz	0.35 Amps
277VAC	60 Hz	0.15 Amps
- HIT Lamps STD Lamp: See Unit Information
- PAR-36 Sealed Beams Opt. PAR-36LED Sealed Beams 5W
- Sealed Lead Calcium Battery
- 6 or 12 Volt Operation
- Maintenance-Free
- 20-Gauge Steel Housing
- Rectangular Polycarbonate Head Units: Standard Beige Powder-Coat Finish
- Round Steel Head Units: Standard Off-White Powder-Coat Finish
- Keyhole Mount
- Red (Power On) LED Indicator
- Test Switch
- UL Listed
- New York City Approved/Calendar #38236

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2CL6S5	6	12	9	6	–	–	–	–	–	(1) S65
2CL6S8	6	18	14	9	7	–	–	–	–	(1) S68
2CL6S10	6	32	24	16	12	10	8	7	6	(1) S610SL
2CL6S16	6	36	27	18	14	11	9	8	7	(2) S68
2CL6S20	6	64	50	32	24	19	16	14	12	(2) S610SL
2CL6S36	6	100	75	50	38	30	25	21	18	(1) S636
2CL12S7	7	36	27	18	14	11	9	8	7	(2) S68
2CL12S10	7	60	45	30	23	18	15	13	11	(2) S610SL
2CL12S15	7	100	75	50	38	30	25	21	18	(1) S1215

†Chicago Approved Available. Contact Factory.

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

## Ordering Information

LS	2	CL	12	S	7	-12
LS-LED H-Halogen	Lamp Heads on Unit (0, 1, 2, 3)	Series	DC Battery Voltage	Battery Type (S – Sealed)	Battery Amp/Hour	Options

For Rectangular Heads with Special HIT Wattage Lamps, add Lamp Wattage as Suffix Number.  
For Round Heads with Special HIT Wattage Lamps, add Suffix “R” and Lamp Wattage.  
For Round Heads with Tungsten Sealed Beam Lamps, add Suffix “S” and Lamp Wattage.  
For Round Halogen Sealed Beam Lamps, add Prefix “H” and Lamp Wattage.  
For Round, PAR36LED Sealed Beam add prefix LS.