

### FEATURES

- 120/277 VAC Operation
- 1.5 Hours of Emergency Illumination
- Integrated Solid State System
- Constant Current, Controlled, Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Maximum Input Rating (120 or 277VAC)  
Standard 1.7 Watts
- Brownout Sensitivity

### EMERGENCY LIGHT

- (2) LM LED Lamps, 3-Watt (Heads on Cover)
- (2) Wedge Base LED Bulb, 1.5-Watt (Heads on Side)
- (2) PAR36 HIT Lamps, 4-Watt (Heads on Side)

### EMERGENCY EXIT

- LED (Indirect)
  - (1) Strip, 120/277 VAC, 1.7-Watt
  - (2) Strips, (-DS), 120/277 VAC, 3.5-Watt
- Light-Emitting Diodes—25+ Year Life
- Illuminates with Uniform Color Brightness
- Indirect Placement for Diffused Legend Output
- Increased LED Brightness Level in Emergency Mode
- Sealed Lead Calcium Battery, 6-Volt Operation (S65)
- Maintenance-Free
- Ceiling, End or Back Mount
- Canopy
- Universal Stencil with Directional Chevron Snapouts
- 20-Gauge Steel Housing with White Powder-Coat Finish
- Easy Installation
- Amber (Power On) Indicator
- Test Switch
- UL Listed



LM2COM

The COM offers Par36 steel heads or mini LED LM heads

### DIMENSIONS

**Height:** 13.3"

**Width:** 12.3"

**Depth:** 2.3"

(Add 12.5" to the Overall Width Dimensions for Round-Head Models)



Models: L, & 4W HIT Heads on the Side. LM heads on cover pictured above

Lamp Type	Lamp Heads	Series	# of Faces	Letter Color	Stencil Color	Housing Color	Options
Blank = 4W H.I.T.	2	COM	1= Single Face	R = Red	W = White	W = White	-U = Universal Faces
L = 1.5W LED			2 = Double Face	G = Green	B = Black	B = Black	-DS = Double Strip
LM = 3W LED							

