

Series Features

- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC)
 - Single Face 3.6 Watts
 - Double Face 5.8 Watts
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- 100–300 Foot Visibility
- Contemporary Styling
- Canopy Standard on Double-Face Signs
- Die Cast Aluminum Construction
- Thin-Edge Black Housing
- Brushed Aluminum Stencil Face
- Directional Chevron Snapouts
- Downlight

Additional Emergency Unit Features

- Integrated Solid State System
- Multi-Rate, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Sealed Nickel Cadmium Battery
- 10-Year Battery Warranty
- 5-Year Shelf Life
- Maintenance-Free
- Test Switch
- Red (Power On) Indicator

Ordering Information

EDXL	1	R	W	W	-FAI
DXL – AC Only EDXL – Emer.	# Faces	Letter Color	Stencil Color	Housing Color	Options
	1 2	Red Green	White Black Aluminum*	White Black*	Factory Options

*Standard

DXL



Options

Add Suffix to Catalog Number

- BZ Audible Buzzer in Emergency Mode (EDXL Only)
- DL Downlight LED
- CPY Canopy (For Single-Face Signs)
- FAI Fire Alarm Interface
- FL Flasher in Emergency Mode (EDXL Only)
- HI High-Intensity LEDs
- TP Tamper-Proof Screws

Master/Slave Options:

- SL Slave (Requires Single-Face EDXL as Power Source)
- REC/S Recessed Mounting for Slave Only
- REC/M Recessed Mounting for Master Only
- REC/MS Recessed Mounting for Master and Slave

Dimensions

- DXL/EDXL
Height: 8.25"
Width: 13.5"
Depth: 2.5"
- CANOPY ONLY
Height: 4.7"
Width: 4.7"
Depth: 0.8"

Accessories

Order Separately

- 63 Wire Guard (for Single-Face Back Mount Only)
- P12W 12" Pendant Kit, White*
- P12B 12" Pendant Kit, Black*
- VDS Vandal-Deterrent Shield (for Single-Face Back Mount XP Only)



UL 924 LISTED



Made in USA