

DXLS



DXLS/EDXLS

Dimensions

DXLS/EDXLS

Height: 8.3"
Width: 12.0"
Depth: 2.3"

CANOPY ONLY

Height: 4.7"
Width: 4.7"
Depth: 0.8"

NEW YORK CITY

Height: 11.0"
Width: 14.5"
Depth: 2.3"

Accessories

Order Separately

63 Wire Guard (for Single-Face Back Mount Only)

VDS Vandal-Deterrent Shield (for Single-Face Back Mount XP Only)



Made in USA

Options














Add Suffix to Catalog Number

- 6 (2) 6VDC Lamps for AC/6VDC Remote Operation
- 12 (2) 12VDC Lamps for AC/12VDC Remote Operation
- CPY Canopy (For Single-Face Signs)
- DMP Damp Location Listing (Damp Label)
- DS Double LED Strips for Increased Illumination or 2 Independent AC Circuit Operation
- HI High-Intensity LEDs
- NY New York City Approved with 8" Letters
- TP Tamper-Proof Screws













Master/Slave Options:

- SL Slave (Requires Single-Face EDXLS as Power Source)
- REC/S Recessed Mounting for Slave Only
- REC/M Recessed Mounting for Master Only
- REC/MS Recessed Mounting for Master and Slave

Series Features

-  • 120/277 VAC Operation
-  • Maximum Input Rating (120 or 277VAC)
Standard 1.7 Watts
DS Option 3.5 Watts
-  • Light-Emitting Diodes – 25+ Year Life
-  • Illuminates with Uniform Color and Brightness
-  • Increased LED Brightness Level in Emergency Mode
-  • Indirect Placement for Diffused Legend Output
-  • Contemporary Styling
-  • Canopy Standard on Double-Face Signs
-  • Die Cast Aluminum Construction
-  • Thin-Edge Black Housing
-  • Brushed Aluminum Stencil Face
-  • Directional Chevron Snapouts
-  • UL Listed

Additional Emergency Unit Features

-  • Integrated Solid State System
-  • Constant Current, Controlled Automatic Charger Circuit
-  • Low-Voltage Battery Cutoff
-  • Brownout Sensitivity
-  • Increased LED Brightness Level in Emergency Mode
-  • Sealed Nickel Cadmium Battery
-  • 5-Year Shelf Life
-  • 10-Year Battery Warranty
-  • Maintenance-Free
-  • 3+ Hours Illumination in Emergency Mode
-  • Test Switch
-  • Red (Power On) Indicator

Ordering Information

EDXLS	1	R	W	W	-DS
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
DXLS – AC Only	1	R ed G reen	W hite B lack A luminum*	W hite B lack*	Factory Options
EDXLS – Emer.	2				

*Standard