

Commercial Emergency Lights

DZN



DZN-PAR

Dimensions

DZN-PAR
 Height: 5.5"
 Width: 12.25"
 Depth: 4.0"

DZN-L
 Height: 5.5"
 Width: 12.25"
 Depth: 4.25"



Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating

120VAC	60 Hz	0.20 Amps
277VAC	60 Hz	0.20 Amps
- DZN-PAR: PAR-36 Type, High-Intensity Tungsten Lamps, 6-Watt
- DZN-L: White LED Lamps
- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free
- Injection-Molded Thermoplastic Housing
- Snap-Together Design for Fast Installation
- Fully Adjustable Lighting Heads
- Off-White Finish
- Wall or Ceiling Mount
- LED Charge Rate Indicator
- Test Switch
- Damp Location Listed
- UL Listed DZN-PAR Only

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
DZN-PAR	6	12	-	-	-	-	-	-	-	(1) S65
DZN-L	1W	12	9	6	4.5	3.5	3	2.5	2	(1) S65

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

Ordering Information

DZN	-PAR
	-L
Series	Lamp Type