

ESDX



Series Features

	<ul style="list-style-type: none"> <li>• 120/277 VAC Operation</li> <li>• Maximum Input Rating (120 or 277VAC) Standard 1.7 Watts</li> <li>• Integrated Solid State System</li> <li>• Constant Current, Controlled Automatic Charger Circuit</li> <li>• Low-Voltage Battery Cutoff</li> <li>• Brownout Sensitivity</li> </ul>
	<ul style="list-style-type: none"> <li>• Light-Emitting Diodes — 25+ Year Life</li> <li>• Illuminates with Uniform Color and Brightness</li> <li>• Indirect Placement for Diffused Legend Output</li> <li>• Increased LED Brightness Level in Emergency Mode</li> </ul>
	<ul style="list-style-type: none"> <li>• Sealed Nickel Cadmium Battery</li> <li>• 5-Year Shelf Life</li> <li>• 10-Year Battery Warranty</li> <li>• Maintenance-Free</li> </ul>
	<ul style="list-style-type: none"> <li>• Ceiling, End or Back Mount</li> <li>• Canopy</li> <li>• Universal Stencil</li> <li>• Directional Chevron Snapouts</li> <li>• 20-Gauge Steel Housing</li> <li>• White Powder-Coat Finish</li> <li>• Easy Installation</li> <li>• UL Listed</li> <li>• 3+ Hours Illumination in Emergency Mode*</li> <li>• Test Switch</li> <li>• LED (Power On) Indicator</li> </ul>

Accessories  
Order Separately

- 63 Wire Guard (for Single-Face Back Mount Only)
- P12W 12" Pendant Kit, White\*
- P12B 12" Pendant Kit, Black\*  
\*Pendant Kits from 12" to 84" Available
- VDS Vandal-Deterrent Shield (for Single-Face Back Mount XP Only)

Dimensions

STANDARD

Height: 7.5"  
Width: 18.0"  
Depth: 2.0"

Options

Add Suffix to Catalog Number

- DMP Damp Location Listing (Damp Label)
- TP Tamper-Proof Screws
- U Universal Face (Additional Backplate — Double-Face Signs Only)
- NY New York City Approved with 8" Letters
- REC Recessed Housing (Single-Face Only)

Ordering Information

ESDX	1	R	W	W	-U
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options Factory Options
	1 2	Red Green	White* Black PM Painted Matte Chrome	White* Black PM Painted Matte Chrome	

See page 72 for SD Information.

\*Standard



Made in USA