

Series Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
120VAC 60 Hz 0.35 Amps
277VAC 60 Hz 0.15 Amps



- HIT Lamps STD Lamp: See Unit Information
- PAR-36 Sealed Beams Opt. PAR-36LED Sealed Beams 5W



- Sealed Lead Calcium Battery (S) or Sealed Nickel Cadmium Battery (N)
- 6 or 12 Volt Operation
- Maintenance-Free



- Contemporary 3-D Design
- 20-Gauge Steel Housing
- Plastic or Steel Lamp Heads
- Rotating & Articulating Swivels
- Universal Mount Backplate
- Beige Powder-Coat Finish Standard
- Red (Power On) LED Indicator
- Test Switch
- UL Listed
- New York City Approved/Calendar #32110

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery	Head Type
		1.5	2	3	4	5	6	7	8		
2ET6S5	6	12	9	6	-	-	-	-	-	(1) S65	Plastic
2ET6S8	9	18	14	9	7	-	-	-	-	(1) S68	Plastic
2ET6S8-8	8	18	14	9	7	-	-	-	-	(1) S68	Steel
H2ET6S10†	12	32	24	16	12	10	8	7	6	(1) S610SL	Steel
H2ET6S16†	12	36	27	18	14	11	9	8	7	(2) S68	Steel
H2ET12S7†	12	36	27	18	14	11	9	8	7	(2) S68	Steel
2ET6N7*	9	18	14	9	7	-	-	-	-	(1) N67F	Plastic
2ET12N7*	9	36	28	18	14	11	9	8	7	(1) N127	Plastic
H2ET6N7*	8	18	14	9	7	-	-	-	-	(1) N67F	Steel
H2ET6N14*	8	36	28	18	14	11	9	8	7	(2) N67F	Steel
H2ET12N7*	12	36	28	18	14	11	9	8	7	(1) N127	Steel

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

*Meets or Exceeds UL 924 Requirements.

Ordering Information

LS	2	ET	6	S	10	-TD
LS - LED Sealed Beam H - Halogen L - LED Wedge Base	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (S - Sealed) (N - Ni Cad)	Battery Amp/Hour	Options

ET



Steel Heads



Plastic Heads

The ET Series of steel emergency lights is an ideal choice for commercial applications where ease of installation, reliability, and moderate remote loads are required.

Dimensions

ET
Height: 12.0"
Width: 13.2"
Depth: 3.8"

Options

Add Suffix to Catalog Number

- A Ammeter*
- BLK Black Finish
- DMP Damp Location
- HTR Heater (Specify 120 or 277 Volt)
- HMC Heads Mounted on Cover
- HOS Heads Mounted on Sides
- OW Designer Off-White Finish (Round Heads Only)
- P2 Cord & Plug for 120VAC Input
- QC Quik-Chek™ Remote Test & Time Delay
- SD Self Diagnostic (See page 72)
- TD Time Delay - Adjusts 1-60 min.
- V Voltmeter*
- W White Finish
- .** Special Lamp Wattage (See page 63)

*Choose Only One

