

### FEATURES

- 120/277 VAC Operation
- 1.5 Hours of Emergency Illumination
- Integrated Solid State System
- Constant Current, Controlled, Automatic Charger Circuit
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Maximum Input Rating (120 or 277VAC) —32 Watts
- Brownout Sensitivity

### EMERGENCY LIGHT

- (2) LM LED Lamps, 3-Watt (Heads on Cover)
- (2) PAR36 LED Sealed Beam, 5-Watt (Heads on Side)
- (2) Wedge Base LED Bulb, 1.5-Watt (Heads on Side)
- (2) PAR36 Incandescent Lamps, 8-Watt (Heads on Side)

### EMERGENCY EXIT

- LED (Indirect)
  - (1) Strip, 120/277 VAC, 1.7-Watt
  - (2) Strips, (-DS), 120/277 VAC, 3.5-Watt
- LED (Direct)
  - (1) Strip, 120 VAC, 3.6-Watt
  - (2) Strips, (-DS), 120/277 VAC, 5.8-Watt
- Light-Emitting Diodes—25+ Year Life
- Indirect Placement for Diffused Legend Output
- Increased LED Brightness Level in Emergency Mode
- Sealed Lead Calcium Battery, 6-Volt Operation
- Maintenance-Free
- Ceiling, End or Back Mount
- Canopy
- Universal Stencil with Directional Chevron Snapouts
- 20-Gauge Steel Housing with White Powder-Coat Finish
- Easy Installation
- Red (Power On) & Green (Trickle Charge) LED Indicator
- Test Switch
- UL Listed



ETX

The ETX is a durable steel combo and provides remote capacity

### DIMENSIONS

**Height:** 13.3"  
**Width:** 12.3"/ 24.8"  
**Depth:** 2.3"

(Add 12.5" to the Overall Width Dimensions for Round-Head Models)



Models: LS, L, & 8W Incandescent Heads on the Side. LM heads on cover pictured above



Lamp Type	Lamp Heads	Series	# of Faces	Letter Color	Stencil Color	Housing Color	Options
Blank = 8W Incandescent	0	ETXFL = Indirect LED	1 = Single Face	R = Red	W = White	W = White	-U = Universal Faces
L = 1.5W LED	1	ETXFLD = Direct-View LED	2 = Double Face	G = Green	B = Black	B = Black	-DS = Double Strip
LS = 5W LED Sealed Beam	2				PM = Painted Matte Chrome	PM = Painted Matte Chrome	
LM = 3W LED							