

Series Features

- Dual-Voltage Transformer for 120/277 VAC Operation
- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Maximum Input Rating (120 or 277VAC) — 36 Watts



EMERGENCY LIGHT

- (2) 6VDC, 6-Watt HIT Lamps (PH)
- (2) 6VDC, 8-Watt PAR-36 Sealed Beams
- (2) PAR36 LED Sealed Beam, 5-Watt
- (2) Wedge Base LED Bulb, 1.5-Watt



EMERGENCY EXIT

- ETXFL — LED (Indirect) 25+ Years
(1) Strip, 120/277 VAC, 3.6-Watt
(2) Strips, (-DS), 120/277 VAC, 3.5-Watt
- ETXFLD — LED (Direct) 25+ Years
Single Face, 120/277 VAC, 3.6-Watt
Double Face, 120/277 VAC, 5.8-Watt



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free

- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts



- 20-Gauge Steel Housing
- Polycarbonate Lamp Enclosures (-PH)
- White Powder-Coat Finish
- Test Switch
- Red (Power On) & Green (Trickle Charge) LED Indicator
- UL Listed

Unit Information

Model Number	Watts per Hour								Replacement Battery
	1.5	2	3	4	5	6	7	8	
ETXFL	32	24	16	12	10	8	7	6	(1) S610SL
ETXFLD	18	14	9	7	-	-	-	-	(1) S68

Ordering Information

LS	2	ETXFL	1	R	W†	W	-PH	-QC
LS-LED*	Emergency Light	Series	# Faces	Letter Color	Stencil Color	Housing Color	Head Type	Options
L-LED 1.5W	0	ETXFL-LED	1	Red	White	White	Blank - Rnd.	Factory Options
LPH-LED 1.5W	1	ETXFLD-LED	2	Green	Black	Black	PH - Plastic Head	
	2			White	PM Painted Matte Chrome	PM Painted Matte Chrome		

*Not Available on PH

ETX



ETX-PH

Rectangular Heads



ETX

Round Heads



Made in USA

Dimensions

HOUSING

Height: 13.3"
Width: 12.3"
Depth: 2.3"
(Add 12.5" to the Overall Width Dimension for Round-Head Models)

Options

Add Suffix to Catalog Number

- DS Double LED Strip (ETXFL)
- HI High-Intensity LEDs (ETXFL & ETXFLD)
- U Universal Face (Additional Backplate — Double-Face Sign Only. Not Available ETXFLD)