

Series Features



- Integrated Solid State System and Switching
- Three-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Single-Voltage Transformer for 120VAC Operation
- Maximum Input Rating
120VAC 60 Hz 1.0 Amps



- Optional PAR-46LED Sealed Beam 5W
- PAR-46 Sealed Beam Lamps, 6-Volt - 21-Watt



- Refillable Nickel Cadmium Battery
- -22° - 140°F Operating Range
- 6-Volt Operation
- 20-25 Year Operating Life



- Rugged 20-Gauge Steel Housing
- Top End Battery Access
- Battery Viewpoint
- Full-Length Piano Hinge with Lock Hasp
- Integral Carrying Handles
- Two-Tone Powder-Coat Finish (Beige & Cocoa) Standard
- Slide-Out Control Chassis
- Test Switch
- Load Cutoff Switch
- Voltmeter
- Amber (Power On), Red (Hi-Charge) and Green (Trickle Charge) Indicators
- UL 924 Listed

Order No. 22 Mounting Shelf

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2GA6N40†	25	100	75	50	32	28	24	20	16	(1) N640
2GA6N50†	25	120	85	55	40	34	28	24	20	(1) N650

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

Ordering Information

LS	2	GA	6	N	40	-QC
LS-LED H-Halogen*	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage (6 - 6-Volt)	Battery Type (N - Ni Cad)	Battery Amp/Hour	Options

*Halogen only available in PAR-36 Sealed Beam

GA



Shown in Standard Two-Tone Beige & Cocoa Finish

Dimensions

GA
Height: 20.5"
Width: 18.5"
Depth: 8.5"

Options

Add Suffix to Catalog Number

- 277 277VAC Input
- BDS Battery Disconnect Switch
- GY Industrial Grey Finish
- P2 Cord & Plug for 120VAC Input
- QC Quik-Chek™ Remote Test & Time Delay
- TD Time Delay - Adjusts 1-60 min.
- ** Special Lamp Wattage (See page 63)

*In Place of Ammeter



Made in USA

