



The LXN series is a self-sufficient EXIT sign that requires no energy, wiring or batteries. The LXN is a great choice for applications where cost to operate are prime concerns.

FEATURES

- No Electrical Power Required
- No Battery Required
- Certified Viewing Distance of 75 Feet
- Surface, Ceiling or Side Mount
- Photo-Luminescent Panel Brightness (Excitation: Fluorescent lamp 54 lx, 60 min. Light source, white F.L. 15w (color temperature 4200K)
- 38 mcd/m² after 90 minutes
- California Energy Commission (CEC) Compliant
- Recharges with a minimum of 5 foot-candle external unfiltered LED, fluorescent, metal halide or mercury vapor illumination.
- Explosion Proof / Waterproof / Corrosion, Mold and Vapor Proof
- 25 Year Expected Life
- Field Installed Chevron Directional Indicators
- Non-Toxic / Non-Radioactive
- Suitable for Damp Locations
- Heavy-Duty Aluminum Frame
- For Integrated Use in Floor Proximity Egress Marking Systems
- Energy Star Compliant
- UL924 Listed



LXN

The LXN series is a self-sufficient EXIT sign that requires no energy, wiring or batteries.

Dimensions

LXN

NO FRAME

Height: 8.5"
 Length: 15.00"
 Depth: .07"

LXN

W/ FRAME

Height: 9.25"
 Length: 15.75"
 Depth: .07"

SERIES	FACES	LETTER COLOR	MOUNTING STYLE
LXN	1	R = RED	U = UNIVERSAL (surface, ceiling or side)
	2	G = GREEN	NF = NO FRAME

