

Sealed Nickel Cadmium Battery Information

- Completely Sealed
- Maintenance-Free
- Active Plate Materials: Nickel Oxide and Metallic Cadmium
- Cylindrical Shape in Fence Construction
- Positive and Negative Lead Wires with Plug-In Connectors
- 5-Year Shelf Life
- 8–10 Years Expected Life in -4°– 158°F
Operating Range (-20°–70°C)



Unit Information

Model Number	DC Volts	Amp Hr.	Watts Per Hour						Dimensions		
			1.5	2	3	4	6	8	L	W	H
N51F	4.8	1.3	4.8	3.8	2.4	—	—	—	3.8	0.9	1.8
N67F	6	7	18	14	9	7	—	—	6.3	1.3	3.6
N71F	7.2	0.6	4	3	2	—	—	—	4	0.7	1.7
N127	12	7	36	28	18	14	9	7	6.3	2.6	3.6

Battery Data May Change Without Notice

Refillable Nickel Cadmium Battery Information

- Battery Filled with Potassium Hydroxide, an Alkaline Solution
- Specific Gravity Does Not Reflect Charged Battery Condition
- 1.180 Nominal Specific Gravity when Filled to Top Level Line
- Immune to Accidental Overcharge
- No Corrosive Fumes
- Refillable for Extended Operating Life
- Nickel Plated, Steel Positive Plates for Low Self-Discharge Rate
- Flame Arrestor Vent Caps
- Nickel-Plated Steel Terminal Post & Hardware
- 20–25 Years Expected Life in -22°–140°F
Operating Range (-30°–60°C)



Unit Information

Model Number	DC Volts	Amp* Hour	Watts per Hour						Dimensions (In.)			
			1.5	2	3	4	6	8	L	W	H	Term.
N640	6	40	100	75	50	32	24	20	9.5	4.8	10.8	
N650	6	50	120	85	55	40	28	20	9.5	4.8	10.8	

Discharge to 87.5% Nominal System Voltage at 68°F Ambient Temperature
*20 Hour Rate

Battery Data May Change Without Notice