

## Series Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 

|        |       |           |
|--------|-------|-----------|
| 120VAC | 60 Hz | 0.20 Amps |
| 277VAC | 60 Hz | 0.20 Amps |



- Optional LED Bulbs 1.5-Watt
- High Intensity Tungsten Lamps, 9-Watt



- Sealed Lead Calcium Battery
- 6 or 12 Volt Operation
- Maintenance Free



- Compact Design
- Injection Molded Polycarbonate Housing
- High Impact, White Finish
- Red (Power On) LED Indicator Light
- Test Switch
- Damp Location
- UL 924 Listed

## Unit Information

| Model Number | Std. Lamp Watt | Watts per Hour |    |    |    | Replacement Battery |
|--------------|----------------|----------------|----|----|----|---------------------|
|              |                | 1.5            | 2  | 3  | 4  |                     |
| 2RC6S20      | 9              | 54             | 48 | 32 | 24 | (2) S610SL          |
| 2RC12S10     | 9              | 54             | 48 | 32 | 24 | (2) S610SL          |

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

## Ordering Information

| 2                  | RC     | 6                  | S                         | 20                     |
|--------------------|--------|--------------------|---------------------------|------------------------|
| Lamp Heads on Unit | Series | DC Battery Voltage | Battery Type (S – Sealed) | Battery Type Amp/ Hour |

## RC



The RC series features a polycarbonate housing in the BBEM-6 family. The RC is great for applications where remotes or extended battery time is needed.

## Dimensions

RC  
Height: 7.5"  
Width: 14.75"  
Depth: 6.75"

## Options

Add Suffix to Catalog Number

- P2 Cord & Plug for 120 VAC Input
- L LED Heads

