

RXL




RXL/ERXL


Dimensions

RECESSED SIGNS


Rough-In
Opening Size: 3" x 15.5"




CEILING RECESSED



WALL RECESSED



CEILING SURFACE



WALL SURFACE

Options

Add Suffix to Catalog Number

- 2CKT (2) Independent AC Circuits
- E End Mount (Use Surface Mount – Ceiling as Base Model)
- SALIDA Spanish Nomenclature
- STAIRS "STAIRS" Nomenclature
- SS Stainless Steel Trim

For Ceiling Recessed Mount Models Only:

- PA Plenum Construction (for Ceiling Recessed models only)



Made in USA

Series Features

- 120VAC Operation Standard
- Maximum Input Rating (120 or 277VAC) 1.7 Watts
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Architectural Grade
- Clean, Contemporary Styling
- Ceiling or Wall Mount
- Recessed or Surface Housing
- Recessed Includes (4) Adjustable Mounting Tabs
- Etched, Clear Acrylic, Edge-Lit Panel
- Silk Screened Letters
- Steel Housing and Trim Plate
- White Powder-Coat Finish
- UL Listed

Additional Emergency Unit Features

- Dual-Voltage Transformer for 120/277 VAC Operation
- Integrated Solid State System
- Constant Current, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Maximum Input Rating (120 or 277VAC) 1.7 Watts
- Light-Emitting Diodes
- Initial Increased LED Brightness Level in Emergency Mode
- Sealed Nickel Cadmium Battery
- 10-Year Battery Warranty
- Maintenance-Free
- 3+ Hours Illumination in Emergency Mode
- Test Switch
- Hanger Bracket Bars (Speed Installation, Provide Housing Adjustment, Can Rotate 90°)
- Amber (Power On) Indicator

Specify Chevron Configuration on all Edge-Lit Signs

Blank = No Chevron


CR = Chevron Right >

CL = Chevron Left <

CD = Chevrons Dual

CRCL = Chevron Right Chevron Left

(Double-Face Only – 1 Chevron per Face)



Ordering Information

ERXL	1	W	R	W**	C	R	-PA
Series	# Faces	Trim Color W hite* B lack B R ass P M Painted Matte Chrome	Letter Color R ed G reen	Background Color Blank – None W – White MB – Mirrored	Fixture Type C eiling W all	Mounting Type R ecessed S urface	Options
RXL – AC Only	1						Factory Options
ERXL – Battery Backup	2						

*Standard