## **Commercial Emergency Lights**

Series Features				
	<ul> <li>Standard Self Diagnostic Feature (see page 72)</li> <li>Integrated Solid State System</li> <li>Multi-Rate, Controlled, Automatic Charger</li> <li>Fused AC Input &amp; DC Output Circuit Protection</li> <li>Lock Out (Automatic Battery Connect)</li> <li>Low-Voltage Battery Cutoff</li> <li>Brownout Sensitivity</li> <li>Dual-Voltage Transformer for 120/277 VAC Operation</li> <li>Maximum Input Rating <ul> <li>120VAC 60 Hz</li> <li>0.35 Amps</li> <li>277VAC 60 Hz</li> <li>0.15 Amps</li> </ul> </li> </ul>			
	HIT Lamps STD Lamp: See Unit Information     PAR-36 Sealed Beams Opt. PAR-36LED Sealed Beams 5W			
Ľ.	<ul> <li>Sealed Lead Calcium Battery</li> <li>6 or 12 Volt Operation</li> <li>Maintenance-Free</li> </ul>			
	<ul> <li>20-Gauge Steel Housing</li> <li>Rectangular Polycarbonate Head Units: Standard White Powder-Coat Finish</li> <li>Round Steel Head Units: Standard White Powder-Coat Finish</li> <li>Keyhole Mount</li> <li>Red (Power On) LED Indicator</li> <li>Test Switch</li> <li>Meets or Exceeds UL 924</li> </ul>			

Unit Information										
Model Number	Std. Lamp Watt	Watts per Hour								Replacement
		1.5	2	3	4	5	6	7	8	Battery
2SD6S5	6	12	9	6	-	-	-	-	-	(1) S65
2SD6S8	6	18	14	9	7	-	-	-	-	(1) S68
2SD6S10	6	32	24	16	12	10	8	7	6	(1) S610SL
2SD6S16	6	36	27	18	14	11	9	8	7	(2) S68
2SD12S7	7	36	18	18	14	11	9	8	7	(2) S68
2SD12S10	7	60	45	30	23	18	15	13	11	(2) S610SL
2SD12S15	7	100	75	50	38	30	25	21	18	(1) S1215

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

## Ordering Information

LS	2	SD	6	S	16	-12
LS-LED H-Halogen	Lamp Heads on Unit (0, 1, 2, 3)	Series	DC Battery Voltage	Battery Type (S – Sealed)	Battery Amp/Hour	Options

For Rectangular Heads with Special HIT Wattage Lamps, add Lamp Wattage as Suffix Number.

For Round Heads with Special HIT Wattage Lamps, add Suffix "R" and Lamp Wattage.

- For Round Heads with Tungsten Sealed Beam Lamps, add Suffix "S" and Lamp Wattage.
- For Round Heads Sealed Beam Lamps, add Suffix "H" and Lamp Wattage.

For Round, PAR36LED Sealed Beam add prefix LS.

See page 72 for Self Diagnostic Information.

SD Not Available on STND HDS with LED



Standard Plastic Heads



Shown in White Finish

Maximizing remote head performance in a low-cost, traditionally styled fixture, the SD Series is capable of powering up to 100 watts in remote lamp loads.





Made in USA

## Dimensions

STANDA	RD HEADS				
Height:	13.8″				
Width:	10.3″				
Depth:	3.5″				
ROUND HEADS					
Height:	15.4″				

 Height:
 15.4"

 Width:
 11.7"

 Depth:
 3.8"

Options

Add Suffix to Catalog Number

-BC Beige & Cocoa Two-Tone Finish -BG Beige Finish -BLK Black Finish -OW Off White Finish -P2 Cord & Plug for 120VAC Input

-\*\* Special Lamp Wattage (See page 63)